



Adhesive PU Foam Manual Type

High quality GNS[®] Adhesive PU Foam Manual Type is offered by China manufacturer GUNUO TIANJIN INDUSTRIAL CO., LTD. Buy Adhesive PU Foam Manual Type which is of high quality directly with low price.

Adhesive PU Foam Manual Type A99 is one component aerosol polyurethane adhesive foam curing swiftly with moisture. Providing very fast and powerful adhesion for various construction materials, especially highly recommended for heat insulation systems. It is designed for easy dispensing through the straw adapter included with each can.

GNS is China manufacturer & supplier who mainly produces GNS[®] Adhesive PU Foam Manual Type with many years of experience. Hope to build business relationship with you. With competitive prices and reliable delivery services, we are expecting become your long-term partner in China. Sincerely look forward to cooperating with you in the near future.

1. PRODUCT FEATURE OF GNS[®] ADHESIVE PU FOAM MANUAL TYPE A99

- Powerful adhesion of polystyrene heat panels (XPS and EPS).
- Instant adhesion and wall plugging within two hours.
- Minimum 14 m² heat insulation panel adhesion for each can.
- Minimum expansion during drying period.
- After dried, no further expansion and shrinkage.
- A lighter material compared to plaster, alternative material, used in heat insulation systems.
- No more extra burden or weight to building.
- High yield up to 50 liters, depending on the humidity and temperature.
- Usable at low temperature like 0 °C
- It does not contain any propellant gases which are harmful to the ozone layer.



GUNUO TIANJIN INDUSTRIAL CO., LTD.
WE HAVE BEEN WORKING HARD!

www.gnspufoamsealant.com

PRODUCT DETAILS



Tel:+86-20-84267539

Email:enquiry@gnsealant.com



GUNUO TIANJIN INDUSTRIAL CO., LTD.
WE HAVE BEEN WORKING HARD!

www.gnsputfoamsealant.com



STABLE FOAM QUALITY

- Pre-expansion
- Good adhesion
- Smooth cell density
- No shrinkage

BETTER INSULATION FACTOR

- Cold insulation
- Sound insulation
- Heat preservation



PU ADHESION FOAM

- Simple application
- Heavy duty bond



GUNUO TIANJIN INDUSTRIAL CO., LTD.
WE HAVE BEEN WORKING HARD!

www.gnspufoamsealant.com

Gun Type



Straw Type



2.PERFORMANCE DATA OF GNS® ADHESIVE PU FOAM MANUAL TYPE A99

| | |
|----------------------|----------------------------|
| Base | Polyurethane |
| Consistency | Stable Foam |
| Curing System | Moisture-cure |
| Tack-Free Time (min) | 6±2min |
| Drying Time | Dust-free after 20-25 min. |

Tel:+86-20-84267539

Email:enquiry@gnsealant.com

| | |
|---------------------------------------|------------------------|
| Cutting Time (hour) | 20-45MIN (+25°C) |
| Yield (L) | 5055L |
| Yield Metric | 14 m ² |
| Shrink | None |
| Post Expansion | None |
| Cellular Structure | > 90% closed cells |
| Specific Gravity (kg/m ³) | 17~22 |
| Shear Strength | 92 kgf/cm ² |
| Temperature Resistance | -40°C~+100°C |
| Application Temperature Range | +5°C~+35°C |
| Colour | Champagne |
| Fire Class (DIN 4102) | B2 |
| Insulation Factor (Mw/m.k) | <30 |
| Compressive Strength (kPa) | >120 |
| Tensile Strength (kPa) | >30 (10%) |
| Adhesive Strength(kPa) | >80 |
| Water Absorption (ML) | 2~3(no epidermis) |
| | <0.5(with epidermis) |

3. APPLICATIONS AREAS OF GNS® ADHESIVE PU FOAM MANUAL TYPE A99

- Best for mounting heat insulation panels(styrofoam) and filling voids during adhesive application.
- Advised for wooden type construction materials adhesion to concrete, metal etc.
- Applications needed minimum expansion.
- Mounting and isolation for frames of windows and doors.



GUNUO TIANJIN INDUSTRIAL CO., LTD.
WE HAVE BEEN WORKING HARD!

www.gnspufoamsealant.com

PRODUCT APPLICATION RANGE





GUNUO TIANJIN INDUSTRIAL CO., LTD.
WE HAVE BEEN WORKING HARD!

www.gnsufoamsealant.com

PRODUCT APPLICATION RANGE





GUNUO TIANJIN INDUSTRIAL CO., LTD.
WE HAVE BEEN WORKING HARD!

www.gnspufoamsealant.com

4. APPLICATION INSTRUCTIONS OF ADHESIVE PU FOAM MANUAL TYPE A99




1 Shake the aerosol can for at least 40 seconds.



2 Clean and moisture the surfaces before use.



3 Fit the plastic applicator on the adaptor.



4 Bottom up and press the adaptor to fill the gap.

5. STORAGE AND SHELF LIFE OF ADHESIVE PU FOAM MANUAL TYPE A99

12 months in unopened packing store in temperature between +5°C to +25°C, Keep in cool, shade and well ventilated area. Always keep the can with the valve pointed upwards.

6. PACKING, SHIPPING AND SERVING OF ADHESIVE PU FOAM MANUAL TYPE A99

Packing: 750ml 500ml 300ml, 12 cans/carton. (For special specifications, please contact us.)

Shipping: Sea or land transportation

Serving: We provide free design service, and you'll get excellent after-sales service, we committed to solving any problems that may occur when you use our products.



GUNUO TIANJIN INDUSTRIAL CO., LTD.
WE HAVE BEEN WORKING HARD!

www.gnspufoamsealant.com

OUR FACTORY



Tel:+86-20-84267539

Email:enquiry@gnsealant.com



GUNUO TIANJIN INDUSTRIAL CO., LTD.
WE HAVE BEEN WORKING HARD!

www.gnspufoamsealant.com



COMPANY PROFILE

- The biggest PU foam manufacturer in Asia
- 19 years export experience
- Sold to 77 countries and areas
- Equipped with 32 advanced full-automatic production line
- 55% market share in China
- Accredited to all kinds certificates

Tel:+86-20-84267539

Email:enquiry@gnsealant.com



GUNUO TIANJIN INDUSTRIAL CO., LTD.

WE HAVE BEEN WORKING HARD!

www.gnsufoamsealant.com

OUR ADVANTAGES



QUALITY

Provide stable and good quality assurance



PACKING

750ml 500ml 300ml, 12 cans/carton.
(For special specifications, please contact us.)



TRANSPORT

Sea or land transportation



TECHNOLOGY

Establish a joint laboratory with WANHUA & DuPont to create products that meet customer needs



COOPERATION

Customer-centric, looking forward to cooperating with all potential customers



SERVICE

We provide free design service, and you'll get excellent after-sales service

7.FAQ

Q: What is the different of the pre-expansion and post expansion? Which one is better?

A: Pre-expansion is better. Post expansion will not only damage the doors and windows after curing, but also it will leads the cost of construction higher because more foam must be cut.

Tel:+86-20-84267539

Email:enquiry@gnsealant.com

Q: Why should we choose a PU foam with good elasticity?

A: Because the PU foam with good elasticity will not damage the doors and windows in hot weather, because its structure inside is better.

