





Weatherproof MS Sealant

As the professional manufacture, we would like to provide you GNS® Weatherproof MS Sealant. And we will offer you the best after-sale service and timely delivery. GNS Weatherproof MS Sealant is the sealant with three different functions sealing, adhesion, gap-filling this sealant can be coated with paint and has good elastic recovery and UV-, heat-, weather-proofing properties suitable for interior and exterior.

GNS is GNS® Weatherproof MS Sealant manufacturers and suppliers in China. We can provide professional service and better price for you. We enjoy a reputation of quality, ethics and service. Sincerely look forward to cooperating with you in the near future.

1.PRODUCT FEATURES OF GNS® WEATHERPROOF MS SEALANT

- •Solvent-free, PVC-free, isocyanate-free, non-toxic, odorless, and non-polluting to the environment;
- •Low modulus, Excellent movement ability 25%;
- •Excellent adhesion to most construction materials, Stone, metal, ceramics and concrete;
- •Can be used in bad weather thanks to good weather-, temperature-, UV-resistance;
- •Can be painted, non-staining waterproof and eco-friendly product;
- •Neutral cure, non-acidic, will not corrode metal or other corrosion-sensitive material.

2.TYPICAL PROPERTIES OF GNS® WEATHERPROOF MS SEALANT

Test Parameter	Unit	Result	
As Supplied Tested at 23 $^\circ \!\!\! \mathbb{C}$ and 50% RH			
Flow (sag or slump)	mm	0	
Skin Time	hour	1	
Mass Loss	%	2.8	
Extrudability	ml/min	186	
Movement Capability	%	±25	



23℃ Tensile/Modulus	Мра	0.9
Elastic Recovery Rate	%	86
Elongation at break	%	400
Max Tensile Strength	MPA	0.6

3.APPLICATIONS AREAS OF GNS® WEATHERPROOF MS SEALANT

• Jointing filling and sealing of all kinds of marble, granite curtain wall engineering and cement prefabrication engineering;

•Concrete expansion joint sealing of road engineering;

•Sealing of prefabricated building joints and high building expansion joints;

•Sealing of window & door frames, Panel seams and ceilings, Water pipes, roof gutters,movable houses and containers

•Interior decoration sealing.

4.APPLICATION INSTRUCTIONS OF GNS® WEATHERPROOF MS SEALANT



--Thoroughly clean and dry surface from oil, dirt and grease. Allow to dry completely before applying silicone.

--Cut the seal at the top of the cartridge and cut the nozzle at a 45° angle, to the size of the gap opening. Screw the nozzle to the top of the cartridge.

--Place the cartridge into a caulking gun.

--Hold the caulking gun at a 45° angle. Press the nozzle opening against the joint, apply steady pressure to the caulking gun and extrude the silicone sealant forcing the sealant into the gap and move in a pushing motion, along the joint in one smooth action.

--Sealant will cure fully in 48 hours. As this point any unwanted sealant can be removed by trimming with a sharp blade, but avoid under cutting the seal.

5.STORAGE AND SHELF LIFE OF WEATHERPROOF MS SEALANT



12 months from manufacture date when store in cool dry locations below 27° C, keep away from heat source and direct sunlight during storage.

6.PACKING, SHIPPING AND SERVING OF PROFESSIONAL USE PU FOAM GUN TYPE


Packing : 300ml plastic cartridge, 24 pcs/ctn, 590ml aluminum sausage, 20 pcs/ctn Shipping: Sea, air or land transportation

Serving: We provide free design service, and you'll get excellent after-sales service, we committed to solving any problems that may occur when you use our products.













COMPANY PROFILE

- The biggest PU foam manufacturer in Asia
- 17 years export experience
- Sold to 72 countries and areas
- Equipped with 32 advanced full-automatic production line
- 50% market share in China
- Accredited to all kinds certificates





7.FAQ

Q: Can I get a sample before order?

A: Sample is available and free, please contact us or send your requirements by email.

Tel:+86-20-84267539



Q: How can you guarantee the quality?

A: We have rigorous quality test system, from raw materials to finished products, the materials must be checked and confirmed by QC department.

