


ST-9820

电脑圆头锁眼机

Electronic Eyelet Button Holer Machine

进一步完善且值得信赖的缝纫机由最先进的电子技术进行最佳控制。生产效率和缝纫质量得到了最高水平的结合。

Further improve and trusted by the most advanced electronic sewing machine technology for optimal control. Production efficiency and quality of sewing the highest level of integration.



机器特征

- 1、达到2,500rpm的世界最高缝纫速度，提高了生产效率
- 2、线迹美观，可缝纫高档产品。
- 3、宽大的机腔可平铺处理布料
- 4、操作简便的操作盘






Features

1. Enhanced productivity with the world's highest max. sewing speed 2,500 rpm.
2. Fine stitches with high-precision stitchpoint.
3. Large arm pocket allowing smooth material handling.
4. Easy-to-use operation panel



技术参数 Technical parameter

规格 Specifications	-00	-01	-02	
			L2230	L1826*1
面线剪线装置 Upper thread trimmer	长线剪切 Long thread cut	长线剪切 Long thread cut	短线剪切 Short thread cut	
底线剪线装置 Lower thread trimmer	无 None	长线剪切 Long thread cut	短线剪切 Short thread cut	
主要用途 Main applications	女装 Men's wear, casual wear, jeans, trousers	男装，休闲装 Men's wear, casual wear	牛仔裤 Jeans	牛仔裤，裤装 Jeans, trousers
其他用途 Other applications	男装，休闲装，牛仔裤，裤装 Ladies' wear	女装，牛仔裤，裤装 Ladies' Wear, jeans, trousers		
功能 Features	剪线装置仅剪切面线。 可缝纫最长为50mm的扣眼。 Only the upper thread is cut by the thread trimmer. Buttonholes up to 50 mm long can be sewn.	剪线装置将较长地剪切所有线头。在缝纫持续过程中可在更长距离内安全把握线尾。很合适要求精确剪切线头或手动剪线的情况。 All the threads are cut long by the thread trimmers. The long thread ends can be securely held in the subsequent process. It is suitable for cases that require accurate short end or manual trimming.	剪线装置将较短地剪切线头，这样可省去手动剪线的麻烦和降低耗线量。 All the threads are cut short by the thread trimmers. This saves the trouble of manual trimming and reduces consumption of the thread.	
缝纫形状 Sewing shape				
缝纫长度 Sewing length	圆头锁眼: 8-50mm 直形钮孔: 5-50mm Eyelet buttonhole: 8-50mm Straight buttonhole: 5-50mm	圆头锁眼: 8-42mm 直形钮孔: 5-42mm Eyelet buttonhole: 8-42mm Straight buttonhole: 5-42mm	22-30 mm *2 L1422 (14-22 mm) *3 L1826 (18-26 mm) *3 L2634 (26-34 mm) *3 L3442 (34-42 mm) *3	18-26 mm *2 L1422 (14-22 mm) *3 L2230 (22-30 mm) *3 L2634 (26-34 mm) *3 L3442 (34-42 mm) *3
缝纫速度 Sewing speed	1,000-2,500rpm			
重量 Weight	机头/Machine head: 120 kg, 操作盘/Operation panel: 0.6 kg, 控制箱/Control box: 14.2-16.2 kg. (由目地的决定)			
电源/耗电量 Power supply / Power consumption	单相100V/200V, 三相200V/220V/380V/400V, 400VA Single phase 100V/200V, 3-phase 200V/220V/380V/400V, 400VA			

*1 适用于中国市场的特殊规格 *2 当剪线装置无法操作时，缝纫长度为5-42mm *3 通过更换量规零件更改范围L1422-L3442。

*4 对于中国市场: DOx558 - NY2#12-#16 (ORGAN) *5 对于中国市场: -00: #16, -01: #14, -02: #18

*1 Special specification for Chinese market *2 Change of the ranges L1422-L3442 is available by replacing gauge parts. (For details, please consult your place of purchase.)

*3 For Chinese market: DOx558 - NY2#12-#16 (ORGAN) *4 For Chinese market: -00: #16, -01: #14, -02: #18