

Bearing No.	Dimensions (mm)								Load Ratings			Limiting Speed nG rpm
	d	D	B	d1	D1	r ₁ mim	r mim	m ⁽¹⁾	Ca (KN)	Coa (KN)	Cua (KN)	
ZKLN 0619.2Z	6	19	12	12	16.5	0.3	0.3	0.02	4.9	6.1	0.226	14000
ZKLN 0624.2RS	6	24	15	14	19.5	0.6	0.3	0.03	6.9	8.5	0.315	6800
ZKLN 0624.2RS PE	6	24	15	14	19.5	0.6	0.3	0.03	6.9	8.5	0.315	6800
ZKLN 0624.2Z	6	24	15	14	19.5	0.3	0.3	0.03	6.9	8.5	0.315	12000
ZKLN 0832.2RS	8	32	20	19	26.5	0.6	0.3	0.09	12.5	16.3	0.6	5100
ZKLN 0832.2Z	8	32	20	19	26.5	0.6	0.3	0.09	12.5	16.3	0.6	9500
ZKLN 1034.2RS	10	34	20	21	28.5	0.6	0.3	0.1	13.4	18.8	0.7	4600
ZKLN 1034.2RS PE	10	34	20	21	28.5	0.6	0.3	0.1	13.4	18.8	0.7	4600
ZKLN 1034.2Z	10	34	20	21	28.5	0.6	0.3	0.1	13.4	18.8	0.7	8600
ZKLN 1242.2RS	12	42	25	25	33.5	0.6	0.3	0.2	17	24.7	0.91	3800
ZKLN 1242.2RS PE	12	42	25	25	33.5	0.6	0.3	0.2	17	24.7	0.91	3800
ZKLN 1242.2Z	12	42	25	25	33.5	0.6	0.3	0.2	17	24.7	0.91	7600
ZKLN 1545.2RS	15	45	25	28	36	0.6	0.3	0.21	17.9	28	1.04	3500
ZKLN 1545.2RS PE	15	45	25	28	36	0.6	0.3	0.21	17.9	28	1.04	3500
ZKLN 1545.2Z	15	45	25	28	36	0.6	0.3	0.21	17.9	28	1.04	7000
ZKLN 1747.2RS	17	47	25	30	38	0.6	0.3	0.22	18.8	31	1.15	3300
ZKLN 1747.2RS PE	17	47	25	30	38	0.6	0.3	0.22	18.8	31	1.15	3300
ZKLN 1747.2Z	17	47	25	30	38	0.6	0.3	0.22	18.8	31	1.15	6600
ZKLN 2052.2RS	20	52	28	34.5	44	0.6	0.3	0.31	26	47	1.74	3000
ZKLN 2052.2RS PE	20	52	28	34.5	44	0.6	0.3	0.31	26	47	1.74	3000
ZKLN 2052.2Z	20	52	28	34.5	44	0.6	0.3	0.31	26	47	1.74	5400
ZKLN 2557.2RS	25	57	28	40.5	49	0.6	0.3	0.34	27.5	55	2.04	2600
ZKLN 2557.2RS PE	25	57	28	40.5	49	0.6	0.3	0.34	27.5	55	2.04	2600
ZKLN 2557.2Z	25	57	28	40.5	49	0.6	0.3	0.34	27.5	55	2.04	4700
ZKLN 3062.2RS	30	62	28	45.5	54	0.6	0.3	0.39	29	64	2.37	2200
ZKLN 3062.2RS PE	30	62	28	45.5	54	0.6	0.3	0.39	29	64	2.37	2200
ZKLN 3062.2Z	30	62	28	45.5	54	0.6	0.3	0.39	29	64	2.37	4300
ZKLN 3572.2RS	35	72	34	52	63	0.6	0.3	0.51	41	89	3.3	2000
ZKLN 3572.2Z	35	72	34	52	63	0.6	0.3	0.51	41	89	3.3	3800
ZKLN 4075.2RS	40	75	34	58	68	0.6	0.3	0.61	43	101	3.75	1800
ZKLN 4075.2Z	40	75	34	58	68	0.6	0.3	0.61	43	101	3.75	3300
ZKLN 5090.2RS	50	90	34	72	82	0.6	0.3	0.88	46.5	126	4.65	1500
ZKLN 5090.2RS PE	50	90	34	72	82	0.6	0.3	0.88	46.5	126	4.65	1500
ZKLN 5090.2Z	50	90	34	72	82	0.6	0.3	0.88	46.5	126	4.65	3000

(1) Weight≈(kg)

(2) Suffix PE: increased tolerances