

Slotted Screwdriver Standard (DIN)					
DIN、ISO2380-1:2004		Hardness: HRC>50°			
Size	Blade dia.	Thickness A	Width B	T1 Position	Torque
0.4x2.5mm	2.5mm	0.38-0.46mm	2.25-2.5mm	0.2	0.4N.m
0.5x3.0mm	3.0mm	0.48-0.56mm	2.75-3.0mm	0.3	0.7N.m
0.8x4.0mm	4.0mm	0.76-0.86mm	3.7-4.0mm	0.5	2.6N.m
1.0x5.5mm	5.0mm	0.96-1.06mm	5.2-5.5mm	0.6	5.5N.m
1.2x6.5mm	6.0mm	1.16-1.26mm	6.14-6.5mm	0.7	9.4N.m
1.2x8.0mm	8.0mm	1.16-1.26mm	7.64-8.0mm	0.7	11.5N.m
1.6x10.0mm	9.0mm	1.54-1.66mm	9.64-10.0mm	1	25.6N.m

PHILLIPS、POZI Screwdriver Standard(DIN)		
DIN、ISO8764-1:2004		Hardness: HRC>54°
Size	Blade Dia.	Torque
PH0、PZ0	3.0-3.1mm	1.0N.m
PH1、PZ1	4.5-5.0mm	3.5N.m
PH2、PZ2	6.0mm	8.2N.m
PH3、PZ3	8.0mm	19.5N.m

SL Screwdriver Standard (ASME)					
ASME B107.15-2002		Hardness: HRC>48°			
Size	Blade dia.	Thickness A	Width B	T1 Position	Torque
3/32	2.5mm	0.36-0.46mm	2.25-2.95mm	0.2	0.4N.m
1/8	3.0mm	0.48-0.64mm	2.75-3.45mm	0.3	1.02N.m
9/64	3.5mm	0.48-0.64mm	3.25-3.95mm	0.3	1.13N.m
5/32	4.0mm	0.59-0.79mm	3.70-4.40mm	0.41	1.92N.m
3/16	5.0mm	0.74-0.94mm	4.70-5.40mm	0.51	3.39N.m
7/32	5.5mm	0.79-0.99mm	5.20-5.90mm	0.51	4.41N.m
1/4	6.0mm	0.92-1.12mm	6.20-6.90mm	0.61	6.55N.m
5/16	8.0mm	1.17-1.37mm	7.64-8.34mm	0.79	12.77N.m
3/8	9.0mm	1.30-1.50mm	9.64-10.3mm	0.86	18.65N.m

PH、PZ Screwdriver Standard(ASME)		
ASME B107.30-2002		Hardness: HRC>48°
Size	Blade Dia.	Torque
PH0、PZ0	3.0MM	1.0N.m
PH1、PZ1	5.0MM	3.5N.m
PH2、PZ2	6.0mm	11.3N.m
PH3、PZ3	8.0mm	24.86N.m