



## PL Series Concrete Batcher

The LUCHEN® PL series concrete batcher is suitable for preparing the mixture of 2-5 types of materials. PL series concrete batcher employing electronic weighing, microcomputer control and digital display, it has the advantages of accurate weighing, high precision, fast speed, reliable control and easy operation. You can rest assured to buy PL Series Concrete Batcher from our factory. We look forward to cooperating with you, if you want to know more, you can consult us now, we will reply to you in time!

### Product Description

The PL series concrete batcher from China factory is suitable for preparing the mixture of 2-5 types of materials. LUCHEN® PL series concrete batcher employing electronic weighing, microcomputer control and digital display, it has the advantages of accurate weighing, high precision, fast speed, reliable control and easy operation, and may be used with JS750, JS1000, JS1500, JS2000, JS3000, JS4000 concrete mixers. LUCHEN® PL series concrete batcher with a reasonable layout and compact structure as well as different modes of discharging, it may be used with appropriate mixers to form combined concrete mixing stations of different types and specifications.



### Main technical parameters of PL series concrete batcher

Model Item	PL1200	PL1600	PL2400B	PL2400	PL3200	PL4800	PL6400
Weigh Hopp	1200L	1600L	2400L	1200L	1600L	2400L	3200L

SHANDONG LUCHEN HEAVY MACHINERY CO., LTD.

Phone:+86-18615455979

E-mail: 337472699@qq.com

er volum e							
Stora ge hoppe r volum e	4 m <sup>3</sup> ×4	7 m <sup>3</sup> ×4	10 m <sup>3</sup> ×4	15 m <sup>3</sup> ×4	25 m <sup>3</sup> ×4	30 m <sup>3</sup> ×4	30 m <sup>3</sup> ×4
Loadi ng width	3200 mm	3100 mm	3100 mm	3250 mm	3500 mm	3500 mm	3500 mm
Type of batchi ng	Single-door ; pneumatic	Single-door ; pneumatic	Single-door ; pneumatic	Double-doo r; pneumatic	Double-doo r; pneumatic	Double-doo r; pneumatic	Double-doo r; pneumatic
Type of weighi ng	Cumulative weighing	Cumulative weighing	Cumulative weighing	Independen t weighing	Independen t weighing	Independen t weighing	Independen t weighing
Upper weighi ng limit	1800 kg	2400 kg	4000 kg	1800 kg	2400 kg	3600 kg	4800 kg
Batchi ng accur acy	±2%	±2%	±2%	±2%	±2%	±2%	±2%
Batchi ng cycle	≤ 40	≤ 40	≤ 60	≤ 60	≤ 60	≤ 60	≤ 60
Power	5.5kw	7.5kw	11kw	7.5kw	11kw	15kw	15kw
Weigh t	5800 kg	6900 kg	7800 kg	11000 kg	14000 kg	15000 kg	17000 kg
Outer dimen sion	13210×200 0×2800	12650×221 0×3120	12650×264 0×3590	13350×300 0×4356	14350×320 0×5030	14350×330 0×5030	14350×348 0×5200



[www.lcheavymachinery.com](http://www.lcheavymachinery.com)

(L * W * H)							
----------------	--	--	--	--	--	--	--