



## Customizable automation electric multi turn valve actuator

Customizable automation electric multi turn valve actuator is specially designed for all multi turn valve applications (linear motion valves)such as globe valve, gate valve, and etc. AOX is a supplier to many large enterprises.There are different "AOX-M" gear boxes can be configured which greatly expanded the

torque range or turn the customizable automation electric multi turn valve actuator into quarter-turn actuator, linear actuator to meet the different requirements.



Zhejiang Aoxiang Auto-Control Technology CO.,Ltd Tel:<u>+86-577-59890750</u> Phone:<u>+86-18967766527</u>

Fax:+86-0577-65921296 E-mail:zjaox@zjaox.com





# Customizable automation electric multi turn valve actuator ntroduction

Customizable automation electric multi turn valve actuator is specially designed for all multi turn valve applications (linear motion valves)such as globe valve, gate valve, and etc. AOX is a Chinese electric actuator manufacturer. Since its launch, customizable automation electric multi turn valve actuator has been continuously enhanced and improved on its quality as well as its features through continuous development by our R&D department.

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd Tel:<u>+86-577-59890750</u> Phone:<u>+86-18967766527</u>

Fax:+86-0577-65921296 E-mail:<u>zjaox@zjaox.com</u>



#### www.aox-privod.com



### Customizable automation electric multi turn valve actuator Parameter (Specification)

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd Tel:<u>+86-577-59890750</u> Phone:<u>+86-18967766527</u>

Fax:+86-0577-65921296 E-mail:<u>zjaox@zjaox.com</u>



#### www.aox-privod.com

Model	Output torque	Speed	Maxshaft diameter	Power	Rated current (A) 50HZ	- Flange	Weight
					three phases		
	N∙m	RPM	mm	W	380V	ISO5210	Kg
AOX-M-007	70	45	Φ28	400	2.42	- F10	32
	70	90		400	2.95		
AOX-M-010	120	35	Φ28	600	2.25	F10	38
	120	70		600	3.18		
	120	105		800	5.15		
AOX-M-020	300	34	Φ40	1100	4.50	- F14	68
	300	67		1100	6.85		
AOX-M-050	450	34	Φ40	1100	9.58	- F14	70
	450	67		1500	14.80		
AOX-M-060	600	34	Φ55	3000	10.89	- F16	103
	600	67		4000	16.50		
AOX-M-080	800	34	Φ55	3000	12.43	- F16	103
	800	67		4000	23.50		
AOX-M-100	1000	34	Φ55	4000	30.20	F16	103


### Customizable automation electric multi turn valve actuator

### **Feature And Application**

Torque Range: 40 - 1000 Nm Direct Output Corrosion level: Epoxy powder coating NEMA 4X corrosion protection is optional. Explosion-proof level: Exd IIC T5 design Motor specification: Class F, with thermal protector up to 135°C Electrical interface: 2\* NPT 3/4 , 1\* NPT1 1/2 Time Lag:N/A Other Function: Torque protection Motor overheat protection Moisture-resistant heaters (anti-moisture device) Reliable electronic system Intelligent block protection Manual / automatic clutch switching Remote control settings Integrated local control unit Mounting base according to ISO5210 Zhejiang Aoxiang Auto-Control Technology CO.,Ltd Fax:+86-0577-65921296 Tel:<u>+86-577-59890750</u> Phone:+86-18967766527 E-mail:zjaox@zjaox.com



**IP68** Enclosure



# Customizable automation electric multi turn valve actuator details

1. Motor of customizable automation electric multi turn valve actuator

Specially designed high starting torque motor, can frequent open the valve from fully closed position. In addition to the three-phase AC motors, single-phase AC are also suitable for customizable automation electric multi turn valve actuator.

2.Different control options meet your specific requirement

Customizable automation electric multi turn valve actuator can be combined with various controls from simple On/off and intelligent modulating control or fieldbus interface.

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd Tel:<u>+86-577-59890750</u> Phone:<u>+86-18967766527</u>