





explosion proof AOX part turn electric actuator

Summary

The "AOX-VR" series explosion proof AOX part turn electric actuator is a new type of small electric actuator. AOX has always focused on the modular design of products. The diversified components ensure that the

products can be assembled according to customer needs, and provide various customized products to meet customer needs.

Product Introduction of the explosion proof AOX part turn electric actuator

The "AOX-VR" series explosion proof AOX part turn electric actuator has an explosion-proof function. The explosion proof class is: Exd II CT5 design valve actuator according to GB/3836, IEC, CU-TR, available in Exd II CT5/Exd a21 IP67 T95°C explosion proof housing (optional ATEX type). ATEX, CCC approved to meet all potentially explosive environments such as oil, gas, chemical, power, metallurgy and the emerging gas industry to name but a few.

Tel: <u>+86-577-59890750</u> Phone: <u>+86-18967766527</u> Fax:+86-0577-65921296

E-mail:<u>zjaox@zjaox.com</u>





Product Parameter (Specification)of the explosion proof AOX part turn electric actuator

Torque range:		50-600nm		
Shell material:		hard aluminum alloy		
Enclosure:		protection grade is IP67 (optional IP68), NEMA 4 and 6		
Motor	power	110 / 220V AC 1phase, 380 / 440V AC 3phase, 50 / 60Hz, ± 10%		
supply:		110 / 220V AC 1pilase, 360 / 440V AC 5pilase, 30 / 60Hz, ± 10%		
Control	power	110 / 220V AC 1phase, 50 / 60 Hz, ± 10%		

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: <u>+86-577-59890750</u> Fax: **+86-0577-65921296**



www.aox-privod.com

supply:					
Motor:	squirrel cage asynchronous motor, insulation class H				
Dryer:	25-30w (220V AC) anti condensation				
Connection port:	2 M20 * 1.5				
Limit switch:	2 x open / close, SPDT, 250V AC 10A				
Mechanical limit:	2 external adjusting bolts				
Auxiliary limit	2 array / alaca CDDT 250V/AC 40A				
switch:	2 x open / close, SPDT, 250V AC 10A				
Torque switch:	2 x open / close, SPDT, 250V AC 10A (optional)				
Traval	90 ° ~ 270 ° \pm 10 ° (specify in advance if the travel is above 90 °); 0 ° ~				
Travel:	270 ° (optional)				
Stall protection /					
operating	built in thermal protection, on 120 $^{\circ}\text{C} \pm 5 ^{\circ}\text{C}$ / off 97 $^{\circ}\text{C} \pm 5 ^{\circ}\text{C}$				
temperature:					
Indicators:	switch indicators				
Outer coating:	dry powder, epoxy polyester				

Model	Maximu m Output	Action Time:	Output Shaft		Motor Class H	Rated Current (A)	Weight
	Torque					50HZ	
	N • M	(90°)	MM		(W)	220V	(kg)
AOX-VR-00 5	50	30	Мах Ф 16	Max 17× 17	10	0.23	4.7
AOX-VR-00 8	80	60	Мах Ф 16	Max 17×	10	0.23	4.7
AOX-VR-01	100	30	Мах Ф 16	Max 17×	15	0.40	5.5
AOX-VR-01 5	150	60	Мах Ф 16	Max 17× 17	15	0.40	5.5
AOX-VR-02 0	200	30	Мах Ф 30	Max 27× 27	60	0.48	15
AOX-VR-03	300	30	Мах Ф 30	Max 27× 27	60	0.52	15
AOX-VR-04 0	400	30	Мах Ф 30	Max 27× 27	60	0.59	15
AOX-VR-06	600	60	Мах Ф 30	Max 27× 27	60	0.52	15


Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: <u>+86-577-59890750</u> Fax: **+86-0577-65921296**



Product Feature And Application of the explosion proof AOX part turn electric actuator

Other manufacturers



The strength accuracy of the main shaft is not high, the matching accuracy of the worm gear and worm is low, and the backlash is large. The output shaft is designed separately, which is not conducive to accuracy and stability.

The "AOX-VR" series



The overall spindle strength accuracy is reliable and stable, the worm gear fits with high accuracy and small return difference. Overall output shaft concentricity and steel and spindle conjoined

Company that manufactures explosion proof AOX part turn electric actuator

Zhejiang Aoxiang Auto-Control Technology Co., Ltd. (formerly known as Rui'an Changhong Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: +86-577-59890750 Fax: +86-0577-65921296




www.aox-privod.com

Fax:+86-0577-65921296

E-mail:<u>zjaox@zjaox.com</u>

Automation Instrument Co., Ltd.) was founded on April 7, 1997. Later, it was changed to Zhejiang Aoxiang Automation Technology Co., Ltd. due to the registered capital of the merger application. The company is located at No. 2608, Development road, Economic Development Zone, Ruian City. It covers an area of 12,300 square meters, with a construction area of 16,200 square meters. The production plant area is 12,600 square meters.



Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: <u>+86-577-59890750</u> Phone: <u>+86-18967766527</u>