



Multi-voltage part turn electric motor operated valve actuator



Is newly designed and developed for especially small ball & plug valves and damper automation. AOX is a **supplier** to many large enterprises. AOX attaches great importance to corporate social responsibility. We continue to seek opportunities for progress, sharing and development with our partners and customers. In addition, all our multi-voltage part turn electric motor

operated valve actuator products and services are handled through customer-centric management, giving the greatest priority to customer satisfaction.



Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: [+86-577-59890750](tel:+86-577-59890750)

Phone: [+86-18967766527](tel:+86-18967766527)

Fax: [+86-0577-65921296](tel:+86-0577-65921296)


E-mail: zjaox@zjaox.com



Multi-voltage part turn electric motor operated valve actuator

Introduction

Multi-voltage part turn electric motor operated valve actuator is suitable for on-off small ball/plug valves and damper automation. AOX is an electric actuator **manufacturer** from **China**. AOX will make great contributions to the future with the best quality multi-voltage part turn electric motor operated valve actuator, new technology and continuous customer service, and strive to become a global leader in valve automation industry in the 21st century.





Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: [+86-577-59890750](tel:+86-577-59890750)

Phone: [+86-18967766527](tel:+86-18967766527)

Fax: [+86-0577-65921296](tel:+86-0577-65921296)

E-mail: zjaox@zjaox.com



Multi-voltage part turn electric motor operated valve actuator

Parameter (Specification)

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: [+86-577-59890750](tel:+86-577-59890750)

Phone: [+86-18967766527](tel:+86-18967766527)

Fax: [+86-0577-65921296](tel:+86-0577-65921296)

E-mail: zjaox@zjaox.com



Model	Max output torque	Operating Time 90°	Drive shaft(mm)		Power (W)	Rated current (A) 220VAC/1ph	Weight (kg)
	N·M		(90°)	Square			
AOX-R-003	30	20	11×11	15.5	8	0.25	2.1
AOX-R-005	50	30	14×14	18	10	0.24	3.6
AOX-R-008	80	30	14×14	18	10	0.26	3.6
AOX-R-010	100	30	17×17	22.5	15	0.40	4.6
AOX-R-015	150	40	17×17	22.5	15	0.42	4.6
AOX-R-020	200	30	22×22	26	60	0.28	13
AOX-R-030	300	30	22×22	26	60	0.32	13.4
AOX-R-040	400	30	22×22	26	60	0.34	13.8
AOX-R-060	600	40	27×27	32.5	60	0.35	14
AOX-R-080	800	40	27×27	32.5	90	0.56	14.3
AOX-R-100	1000	40	27×27	32.5	90	0.59	14.5
AOX-R-160	1600	60	Max Φ40	65	90	0.60	68
AOX-R-200	2000	60	Max Φ40	65	90	0.62	68
AOX-R-300	3000	120	Max Φ40	65	90	0.64	68
AOX-R-400	4000	200	Max Φ40	65	90	0.66	68
AOX-R-500	5000	200	Max Φ40	65	90	0.67	68

Multi-voltage part turn electric motor operated valve actuator

Feature And Application

Torque range: 30~5000N.m

Control method: On and off / modulating type/ Intelligent type

Weight: 2.1 KGS~68 KGS

Voltage: AC110~265V , AC / DC 24V Multi voltage input

Applicable valve : Ball Valve (DN15-DN200); Butterfly Valve (DN25-DN400)

Mounting Flange (ISO 5211): F04/F05/F07/F10/F12/F14/F16

Input/output signal (modulating type):4-20mA(std configuration);0-10V &2-10V is optional.

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: [+86-577-59890750](tel:+86-577-59890750)









Phone: [+86-18967766527](tel:+86-18967766527)

Fax: [+86-0577-65921296](tel:+86-0577-65921296)

E-mail: zjaox@zjaox.com











Comparison With Other Products (Eight Major Improvements)

Other manufacturers	Description	Other manufacturers	Description
	The gasket is easily deformed by temperature and other reasons, resulting in reduced sealing performance, which is not very aesthetically pleasing.		The combination of upper and lower cover adopts concave and convex structure, inner gasket O-ring, strong sealing performance, beautiful appearance, high protection level, more convenient for debugging and wiring, only need to open the upper cover
	The use of chemical adhesives may lead to ageing and water ingress due to high temperatures and pressures on site, and the plastic and glazing are easily damaged.		Convex mirror surface, no water accumulation; and continuous valve opening indication, more convenient observation, external metal, not easy to damage
	Ordinary terminal blocks, in the field of temperature difference or vibration, will cause the fastening screws to loosen, resulting in poor contact phenomenon.		The use of self-actuating pop-up terminals guarantees absolute reliability and is a symbol of high-end products.
	The gearboxes are made of plastic, and individual manufacturers use powder alloys for the gears, which are prone to wear.		The gearbox is made of 40Cr, refined by three heat treatments, more solid and reliable

Patent No.: ZL 2013 3 0145624.9
ZL 2013 3 0145691.0
ZL 2013 3 0112341.4
ZL 2013 3 0112302.4



Comparison With Other Products (Eight Major Improvements)

	Spanner not fixed to the case, easily lost		The spanner is placed on the box, so it is not easily lost on site and is easy to use
	Regulated modules have built-in, electronic components that are affected by the temperature generated during operation.		The adjustment module is mounted externally and the bare board dissipates heat better, solving the contradiction that the maximum temperature of the actuator is 120° C while the temperature of the electronic components of the module is only 55° C. The weak control power supply is used and the quality of the module will not be affected by the unstable voltage on site.
	The screws of other manufacturers' housings are not equipped with an anti-dislodgement function, which can easily lead to the dislodgement of the screws during maintenance when removing the housing at height.		The top cover bolts are specially designed not to come off during maintenance and installation. All external bolts are made of stainless steel and will not rust
	Other manufacturers use M3 screws for unrealistic positioning, inaccurate, slippery threads, M3 spanners are not easy to find on site and other drawbacks.		AOX has improved the electrical cam structure by integrating the four cams into two and isolating them with a butterfly shaped bullet, topped with an anti-loosening nut, and using imported Omron travel switches.

Patent No.: ZL 2013 3 0111005.8
ZL 2013 3 0111120.5
ZL 2013 3 0111352.0



Multi-voltage part turn electric motor operated valve actuator

Details

1. Firm corrosion-resistant housing: The shell of multi-voltage part turn electric motor operated Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: +86-577-59890750

Phone: +86-18967766527

Fax: +86-0577-65921296

E-mail: zjaox@zjaox.com



www.aox-privod.com

valve actuator is made of aluminum alloy, with anodic oxidation treatment and polyester powder coating. It is strong corrosion-resistant and enclosure IP67,NEMA 4 and 6, IP68 is optional.

2.Optional space heater:It is used for controlling temperature to avoid condensing internal of housing and keep dry.

3.External modulating module for multi-voltage part turn electric motor operated valve actuator:Increase the space of the module, it will make the module more stable and have a longer service life.

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: [+86-577-59890750](tel:+86-577-59890750)

Phone: [+86-18967766527](tel:+86-18967766527)

Fax: [+86-0577-65921296](tel:+86-0577-65921296)

E-mail: zjax@zjax.com