



## Water proof 1/4 turn electric actuator



AOX water proof 1/4 turn electric actuator are suitable for on-off small ball/plug valves and damper automation .The innovative product design concepts of AOX water proof 1/4 turn electric actuator in practical applications have gotten multiparty attention and recognition. AOX has its own factory in China.Choosing AOX is a professional choice.We will be happy to provide you with quality products and efficient service.



Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: [+86-577-59890750](tel:+86-577-59890750)

Phone: [+86-18967766527](tel:+86-18967766527)


Fax: [+86-0577-65921296](tel:+86-0577-65921296)

E-mail: [zjaox@zjaox.com](mailto:zjaox@zjaox.com)



## AOX water proof 1/4 turn electric actuator Introduction

AOX water proof 1/4 turn electric actuator is widely used for modulating and open-close duty in process technology. AOX water proof 1/4 turn electric actuator is newly designed and developed for especially small ball & plug valves. AOX is a supplier of many large enterprises. AOX water proof 1/4 turn electric actuators protection level can reach IP67, and AOX water proof 1/4 turn electric actuator waterproof performance is one of the best in the current product.



Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: [+86-577-59890750](tel:+86-577-59890750)

Phone: [+86-18967766527](tel:+86-18967766527)

Fax: [+86-0577-65921296](tel:+86-0577-65921296)


E-mail: [zjaox@zjaox.com](mailto:zjaox@zjaox.com)



### Product Image



### Product Image





## AOX water proof 1/4 turn electric actuator Parameter (Specification)

Model	Max output torque	Operating Time 90°	Drive shaft(mm)		Power	Rated current (A)	Weight
	N·M	( 90°)	Square	Deep	(W)	220VAC/1ph	(kg)
AOX-R-003	30	20	11×11	15.5	8	0.25	2.1
AOX-R-005	50	30	14×14	18	10	0.24	3.6
AOX-R-008	80	30	14×14	18	10	0.26	3.6
AOX-R-010	100	30	17×17	22.5	15	0.40	4.6
AOX-R-015	150	40	17×17	22.5	15	0.42	4.6
AOX-R-020	200	30	22×22	26	60	0.28	13
AOX-R-030	300	30	22×22	26	60	0.32	13.4
AOX-R-040	400	30	22×22	26	60	0.34	13.8
AOX-R-060	600	40	27×27	32.5	60	0.35	14
AOX-R-080	800	40	27×27	32.5	90	0.56	14.3
AOX-R-100	1000	40	27×27	32.5	90	0.59	14.5
AOX-R-160	1600	60	Max Φ40	65	90	0.60	68
AOX-R-200	2000	60	Max Φ40	65	90	0.62	68
AOX-R-300	3000	120	Max Φ40	65	90	0.64	68
AOX-R-400	4000	200	Max Φ40	65	90	0.66	68
AOX-R-500	5000	200	Max Φ40	65	90	0.67	68

## AOX water proof 1/4 turn electric actuator Feature And Application

Power: AC85 265V ,AC380V, AC/DC24V multi power input,  
AC 220V/110V/AC 24V/DC 24V single power input.

Environment temp: -20℃~70℃.

Related humidity: <90%(25℃).

Environment: Without any high corrosion and explosion medium.

Working time: S1 long time standard for both On-off and modulating type.

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: [+86-577-59890750](tel:+86-577-59890750)









Phone: [+86-18967766527](tel:+86-18967766527)

Fax: [+86-0577-65921296](tel:+86-0577-65921296)

E-mail: [zjaox@zjaox.com](mailto:zjaox@zjaox.com)











## Comparison With Other Products (Eight Major Improvements)

Other manufacturers	Description	Other manufacturers	Description
	The gasket is easily deformed by temperature and other reasons, resulting in reduced sealing performance, which is not very aesthetically pleasing.		The combination of upper and lower cover adopts concave and convex structure, inner gasket O-ring, strong sealing performance, beautiful appearance, high protection level, more convenient for debugging and wiring, only need to open the upper cover
	The use of chemical adhesives may lead to ageing and water ingress due to high temperatures and pressures on site, and the plastic and glazing are easily damaged.		Convex mirror surface, no water accumulation; and continuous valve opening indication, more convenient observation, external metal, not easy to damage
	Ordinary terminal blocks, in the field of temperature difference or vibration, will cause the fastening screws to loosen, resulting in poor contact phenomenon.		The use of self-actuating pop-up terminals guarantees absolute reliability and is a symbol of high-end products.
	The gearboxes are made of plastic, and individual manufacturers use powder alloys for the gears, which are prone to wear.		The gearbox is made of 40cr, refined by three heat treatments, more solid and reliable

Patent No.: ZL 2013 3 0145624.9  
 ZL 2013 3 0145691.0  
 ZL 2013 3 0112341.4  
 ZL 2013 3 0112302.4



## Comparison With Other Products (Eight Major Improvements)

	Spanner not fixed to the case, easily lost		The spanner is placed on the box, so it is not easily lost on site and is easy to use
	Regulated modules have built-in, electronic components that are affected by the temperature generated during operation.		The adjustment module is mounted externally and the bare board dissipates heat better, solving the contradiction that the maximum temperature of the actuator is 120° C while the temperature of the electronic elements of the module is only 65° C. The weak control power supply is used and the quality of the module will not be affected by the unstable voltage on site.
	The screws of other manufacturers' housings are not equipped with an anti-dislodgement function, which can easily lead to the dislodgement of the screws during maintenance when removing the housing at height.		The top cover bolts are specially designed not to come off during maintenance and installation. All external bolts are made of stainless steel and will not rust
	Other manufacturers use M3 screws for unrealistic positioning, inaccurate, slippery threads, M3 spanners are not easy to find on site and other drawbacks.		AOX has improved the electrical cam structure by integrating the four cams into two and isolating them with a butterfly shaped bullet, topped with an anti-loosening nut, and using imported Omron travel switches.

Patent No.: ZL 2013 3 0111005.8  
 ZL 2013 3 0111120.5  
 ZL 2013 3 0111352.0



## AOX water proof 1/4 turn electric actuator details

Zhejiang Aoxiang Auto-Control Technology CO.,Ltd

Tel: +86-577-59890750

Phone: +86-18967766527

Fax: +86-0577-65921296

E-mail: [zjaxox@zjaxox.com](mailto:zjaxox@zjaxox.com)



Our Advantages

**Other**



**AOX**



The debugging is quicker and more convenient. AOX-R series water proof quarter turn electric actuator integrates the four cams into two pieces by improving the electric cam structure, and is separated by a butterfly spring. The upper part is pressed with a lock nut and an inlet potentiometer is used.

**Other**



**AOX**



The control line of AOX-R series water proof quarter turn electric actuator complies with single-phase or three-phase power supply standards, and the line layout is compact and reasonable.

AOX water proof 1/4 turn electric actuator ISO 5211 mounting base:

Wide, easy mounting base standard to ISO5211/DIN3337.

AOX water proof 1/4 turn electric actuator Well sealing:

By improving the [concave-convex structure](#) of the shell and cover, and sealing with silicone rubber to provide water proof IP67 and IP68(option).