

■ High-frequency Microwave Sensor **PD-V4** instruction

CEREDI® REACH





PD-V4 360° 5.8GHz Microwave Motion Sensor

Application

- Intelligent switch
- Automatic light
- Intruder detect

Feature and advantage

- Low wireless power output
- Low power consumption
- Non-contact detection
- Easy to match with the external circuit
- High anti-jamming ability Suit various harsh environment

Antenna Beam Pattern(Omni-directional)

Low noise output


PD-V4 360° 5.8GHz Microwave Motion Sensor is a C-Band Bi-Static Doppler transceiver modlue .lt adopts built-in Resonator Oscillator (CRO) amplificated signal external circuit.More sensitive and lower power consumption than V2. It is convenient for the customers to develop various products.

This module is ideally suiable for occupancy sensor in automatic lighting switches. It can also be used for ceiling mount intruder detectors.


According with EN 300440-V2.1.1 EN 62479: 2010,RED directive-2014/53/eu


According with FCC Part 15.249

According with EN 62321,ROHS directive-2011/65/eu According with REACH directive-1907/2006/ec



Products size





Block diagram and connection



Parameter	Notes	Min	Тур	Max	Units
Frequency Setting	1	5.75	5.80	5.85	GHz
Radiated Power (EIRP)	1	0.18	0.20	0.22	mW
Settling Time		5	10	20	μSec
Received Signal Strength	2	150	200	300	μVp-p
Noise	3	0.5		2	mVrms
Supply Voltage		4.75	5.00	5.25	VDC
Current Consumption		12	12.5	13.5	mA
Pulse Repetition Frequency	4	2.0	2.2	3.0	KHz
Pulse Width	4	15	50	70	μSec
Operating Temperature		-15	22	90	℃
Weight		4.5	4.8	5.3	g

Note1: The radiated emissions is designed to meet FCC rules.

Note2: The Received Signal Strength (RSS) is measured at the total 1 Ways path loss of 64dB.

Note3: The noise voltages are measured from 10Hz to 100Hz at the Output port, inside an Anechoic chamber.

Note4: Pulse operation

Ningbo Pdlux Electronic Technology CO.,Ltd

Add: 17F, Commerce Building of NingBo, No 588, South Tiantong Rode, Yinzhou District, Ningbo, China

Tel: 86-574-83008608(20 lines) Fax: 86-574-83008609 Email: pdlux@pdlux.com Web: www.pdlux.com

www.pdlux.com Tel: 86-574-83008608(20 lines)