

US TYPE High Tensile Forged Shackle G2130



Feature of US TYPE High Tensile Forged Shackle
G2130
US type
Material: 40cr
Forged Steel
Ultimate load: W.L.L*4
Surface Treatment: Self-color, Zinc pleated, Hot dip
dalvanized,
Trivalent chromium plating zinc, powder coating

US TYPE High Tensile Forged Shackle G2130 Feature

US type
Material: 40cr
Forged Steel
Ultimate load: W.L.L*4
Surface Treatment: Self-color, Zinc pleated, Hot dip dalvanized,
Trivalent chromium plating zinc, powder coating

US TYPE High Tensile Forged Shackle G2130 Specification

Nominal Size	Working load limit(tons)	Dimensinons(mm)									Weight each
		A	B	C	D	E	F	G	H	I	
3/16	1/3	9.656	3522.44	8515.214	237.224	94.850	03				
1/4	1/2	11.97	8528.76	3519.815	546.732	56.350	05				
5/16	3/4	13.59	6531	7.852	1.319	153	37.37	850.1			
3/8	1	16.81	1.236	69.652	6.223	163	45.29	650.15			
7/16	1-1/2	19.11	2.742	911.229	526.974	51.51	1.20	22			
1/2	2	20.61	6	47.81	2.733	330.283	558.51	2.70	36		
5/8	3-1/4	26.91	9.160	516	42.93	8.110	674.51	7.50	76		
3/4	4-3/4	31.82	2.471	519.151	46	126	89	20.61	23		
7/8	6-1/2	36.62	5.484	22.45	8	53	148	102	24.61	79	
1	8-1/2	42.92	8.795	525.46	8.560	516	7	119	26.92	57	
1-1/8	9-1/2	46	31.81	08	28.77	4	68.51	90	131	31.83	75

1-1/4	12	51.535.1119	31.882.576	210	146	35.15.31
1-3/8	13-1/2	57	38.1133	35.192	84	233 162 38.17.18
1-1/2	17	60.541.4146	38.198.592	254	175	41.19.43
1-3/4	25	73	51	178	44.5127	106 313 225 57 15.4
2	35	82.557	197	51	146	122 348 253 61 23.7
2-1/2	55	44.6105	70	267	66.5184	145 453 327 44.61
3	85	127	82.5330	76	200	165 546 365 92 70
3-1/2	120	133	95.5372	92	229	203 626 419 105 120
4	150	140	108	368	104	254 229 653 468 116 153

