



### **Press On And Press Fit Solid Tire**

Our press on and press fit solid tire have passed the ISO9001 Quality certification. And we insist on quality first, service first, we promise to all customers inquiry will be replied within 24 hour work days in time. We have always believed in establishing long term and mutually benefit business relationship with our customers.

Our press on and press fit solid tire have passed the ISO9001 Quality certification. And we insist on quality first, service first, we promise to all customers inquiry will be replied within 24 hour work days in time. We have always believed in establishing long term and mutually benefit business relationship with our customers.

### **Product Introduction**

Press on and press fit solid tire are equipped with advanced manufacturing equipment from smelting, extrusion, cutting, molding and vulcanization. Various raw materials such as rubber, nylon lines and carbon black are purchased only from top suppliers, which effectively guarantees the stable quality of the products.

### **Product Parameter (Specification)**

规格 Size		花纹	Load Capacity(kg) 最大负荷 Balance Forklift 平衡叉车				其他工业 车辆 16km/h
英制 (inch)	公制 (mm)		10km/h		16km/h		
			Drive 驱动轮	Steer 转向轮	Drive 驱动轮	Steer 转向轮	
9X5X5	228.6X127X127	SM	890	790	850	680	680
10X4X6 1/2	254X101.6X165.1	SM	720	640	690	555	555
10X5X6 1/2	254X127X165.1	SM	940	840	900	725	725
10X6X6 1/2	254X152.4X165.1	SM	1160	1030	1110	895	895
10X5X6 1/4	254X127X158.8	SM	950	850	910	735	735
10X6X6 1/4	254X152.4X158.8	SM	1170	1050	1120	910	910
10 1/2X5X5	266.7X127X127	SM	1020	905	980	785	785
10 1/2X6X5	266.7X152.4X127	SM	1295	1150	1240	1000	1000
10 1/2X5X6 1/2	266.7X127X165.1	SM	1000	890	950	770	770
10 1/2X6X6 1/2	266.7X152.4X165.1	SM	1240	1100	1185	950	950
12X4 1/2X8	304.8X114.3X203.2	SM	950	840	900	730	730
12X5X8	304.8X127X203.2	SM	1030	915	980	800	800
13 1/2X5 1/2X8	342.9X139.7X203.2	SM	1400	1250	1340	1080	1080
14X4 1/2X8	355.6X114.3X203.2	SM	1090	970	1040	840	840
15X5X111/4	381X127X285.8	SM	1290	1150	1230	990	990
15X6X111/4	381X152.4X285.8	SM	1420	1270	1360	1100	1100
15 1/2X5X10	393.7X127X254	SM.TR	1360	1210	1300	1050	1050
15 1/2X6X10	393.7X152.4X254	SM	1730	1540	1655	1330	1330
16X5X10 1/2	406.4X127X266.7	SM.TR	1400	1250	1340	1080	1080
16X6X10 1/2	406.4X152.4X266.7	SM.TR	1780	1580	1700	1370	1370
16X7X10 1/2	406.4X177.8X266.7	SM	2150	1910	2050	1655	1655
16 1/4X5X11 1/4	412.8X127X285.8	SM.TR	1415	1260	1390	1110	1110
16 1/4X6X11 1/4	412.8X152.4X285.8	SM.TR	1800	1630	1750	1420	1420
16 1/4X7X11 1/4	412.8X177.8X285.8	SM	2200	1960	2100	1705	1705
17X5X12 1/8	431.8X127X308	SM	1460	1300	1400	1120	1120
18X5X12 1/8	457.2X127X308	SM.TR	1530	1360	1460	1170	1170
18X6X12 1/8	457.2X152.4X308	SM.TR	1950	1740	1860	1500	1500
18X7X12 1/8	457.2X177.8X308	SM.TR	2370	2110	2270	1820	1820
18X8X12 1/8	457.2X203.2X308	SM.TR	2790	2480	2670	2150	2150
18X9X12 1/8	457.2X228.6X308	SM.TR	3210	2850	3070	2470	2470
20X8X16	508X203.2X406.4	SM.TR	2790	2480	2670	2150	2150
21X7X15	533.4X177.8X381	SM.TR	2670	2380	2550	2050	2050
21X8X15	533.4X203.2X381	SM.TR	3140	2795	3000	2420	2420
21X9X15	533.4X228.6X381	SM	3620	3220	3460	2890	2890
22X8X16	558.8X203.2X406.4	SM.TR	3260	2900	3110	2505	2505
22X9X16	558.8X228.6X406.4	SM.TR	3700	3340	3590	2890	2890
22X12X16	558.8X304.8X406.4	SM.TR	5235	4660	5000	4030	4030
28X12X22	711X304.8X558.8	SM	6120	5450	5900	4725	4725
28X14X22	711X355.6X558.8	SM	7200	6430	6950	5990	5990
28X16X22	711X406.4X558.8	SM	8250	7345	7930	6805	6805
36X9X30	914.4X228.6X762	SM	5365	4630	5005	4005	4005
36X10X30	914.4X254X762	SM	6570	5750	6170	5150	5150

### Product Feature And Application

Press on and press fit solid tire using the world's leading tire formula technology,coupled with the latest environmentally materials and high-quality natural rubber,the tire compound is endowed with extremely low heat generation characteristics.

### Product Details

Press on and press fit solid tire introducing the design concept of radial tire pattern,transverse grooves,with excellent anti-fatigue performance and long service life.



**Product Qualification**



**Deliver,Shipping And Serving**



**FAQ**

- A. what is the MOQ?- One 20 feet container, and can be mixed.
- B. What warranty for the tyres?- Within 2 years after the date of B/L.