



#### **ESD PEEK Rod**

As A Professional ESD PEEK Rod Manufacture, You Can Rest Assured To Buy ESD PEEK Rod From Our Factory And Hengbo® Will Offer You The Best After-Sale Service And Timely Delivery.

### **Product Description**

Jiangsu Hengbo® Composite Materials Co.,Ltd is a leading China ESD PEEK Rod manufacturer, supplier and exporter.

ESD PEEK Rod is well known as having the best balance of chemical resistance, wear resistance and heat resistance among all thermoplastic. Hengbo® have been manufacturing the ESD PEEK Rod since 2019. We are expecting become your long-term partner in China.

### **Product Parameter (Specification)**

| Properties                        | Unit         | Test Method |  |
|-----------------------------------|--------------|-------------|--|
| Physical Properties               |              |             |  |
| Density                           | 1.31g/cm3    | ISO1183     |  |
| Water absorption                  | 0.04%        | ISO62-1     |  |
| Shore D Hardness                  | 88           | ISO868      |  |
| Thermal Properties                |              |             |  |
| Glass transition temperature      | <b>152</b> ℃ | ISO 11357   |  |
| Melting point                     | 373℃         | ISO 11357   |  |
| Heat Deflection temperature       | 315℃         | ISO75A-f    |  |
| Mechanical Properties             |              |             |  |
| Tensile Strength                  | 180 Mpa      | ISO527      |  |
| Tensile Modulus                   | 11 GPa       | ISO527      |  |
| Tensile Elongation                | 2.7%         | ISO527      |  |
| Flexural Strength                 | 278 MPa      | ISO178      |  |
| Flexura Modulus                   | 12 GPa       | ISO178      |  |
| Izod Impact Strength (Notched)    | 6 kj/m-2     | ISO179/leA  |  |
| Izod Impact Strength (un-Notched) | 60 kj/m-2    | ISO180/IU   |  |
| Electric Properties               |              |             |  |



| Volume Resistivity    | 106~108Ωcm     | IEC60093   |
|-----------------------|----------------|------------|
| Dielectric Strength   |                | IEC6243    |
| Flow Properties       |                |            |
| Melt Viscosity @400°C | 6 / 400°C,5kgs | ISO 1133   |
| Other Properties      |                |            |
| Flammability          | V-0            | UL94/0.8mm |
| Friction Coefficient  | 0.4            | 2.0ksi-fpm |

## **Product Feature And Application**

ESD PEEK Rod are used for Industrial, automotive, medical, AEROSPACE and etc



### **Product Details**

Diameter of ESD PEEK Rod are from 6mm to 150mm and length is 1000mm



### **Product Qualification**

ESD PEEK Rod are approved by REACH and RoHS



# **Deliver, Shipping And Serving**

We have 6 lines for PEEK rod, we will delivery the cargo as required.

