



PEEK Screw

The following is an introduction to PEEK Screw, I hope to help you better understand PEEK Screw. Welcome new and old customers to continue to cooperate with Hengbo® to create a better future together!

Product Description

As the professional manufacture, Hengbo® would like to provide you high quality PEEK Screw. And we will offer you the best after-sale service and timely delivery.

PEEK Screw is well known as having the best balance of chemical resistance, wear resistance and heat resistance among all thermoplastic. We have been manufacturing the PEEK Screw since 2019. We are expecting become your long-term partner in China.

Product Parameter (Specification)

Properties	Unit	Test Method	
Physical Properties			
Density	1.31g/cm3	ISO1183	
Water absorption	0.07%	ISO62-1	
Shore D Hardness	85	ISO868	
Thermal Properties			
Glass transition temperature	152℃	ISO 11357	
Melting point	373℃	ISO 11357	
Heat Deflection temperature	170℃	ISO75A-f	
Mechanical Properties			
Tensile Strength	102 Mpa	ISO527	
Tensile Modulus	4.2 GPa	ISO527	
Tensile Elongation	45%	ISO527	
Flexural Strength	190 MPa	ISO178	
Flexural Modulus	4.1 GPa	ISO178	
Izod Impact Strength (Notched)	7 kj/m-2	ISO179/leA	
Izod Impact Strength (un-Notched)	-		
Electric Properties			
Volume Resistivity	1016Ωcm	IEC60093	



Dielectric Strength	21 KV/MM	IEC6243	
Flow Properties			
Melt Viscosity @400°C	11/ 400°C,5kgs	ISO 1133	
Other Properties			
Flammability	V-0	UL94/0.8mm	
Friction Coefficient	0.5	2.0ksi-fpm	

Product Feature And Application

PEEK Screw are used for Industrial, automotive, medical, AEROSPACE and etc



Product Details

Diameter of PEEK Screw is M2\2.5\3\4\5\6\8\10\12\16 and etc



Product Qualification

PEEK Screw are approved by REACH and RoHS



Deliver, Shipping And Serving

We have 1 line for PEEK Screw, we will delivery the cargo as required.