

型号	配带功率P (KW)	流量Q(m³/h)	扬程H(m)	转速n(r/min)	最高效率η%	汽蚀余量NPSH(m)	叶轮直径 D(mm)	重量( kg)
20A-L	0.75-7.5	1.8-9	7-35.5	1400-3000	40	2.5-3	152	46
50B-L	2.2-15	11.5-65	8.5-46	1400-2800	62	2.5-5.5	190	90
50B-LR	2.2-15	9-61	3-35	1200-2600	48	2.75-4.5	190	76
75C-L	3-30	21.6-136.8	7-47	900-2400	57	3-6	229	200
75C-LR	3-30	28-155	8-43	1100-2300	60	3-5	229	170
100D-L	5.5-60	46.8-324	7-48	800-1600	65	2.5-5.5	305	370
100D-LR	5.5-60	54-288	12-38	800-1500	65	2.5-6	305	320
150E-L	15-120	126-568	10-51	800-1500	60	2.5-6	381	750
150E-LR	15-120	72-576	4-38	800-1300	65	2.5-5.5	381	
300S-L	45-560	568-2538	8-60	400-950	78	3-10	653	
300S-LR	45-560	432-1900	7-41	400-800	81	3-8	653	
350S-L	55-560	650-2800	10-59	400-840	81	3-10	736	
350S-LR	55-560	720-2844	10-41	400-700	86	3-7	736	