



Self-contained Hopper Loader

AUMAX AML-400G three phase combined vacuum hopper loader machine is special designed for conveying plastic resin materials in plastic injection molding industry. This vacuum auto loader equipped with three phase induction type air pump. The self-contained hopper loader machine has reversal function to clean the dust on the filters. The capacity of AML-400G

hopper loader is 300kg ~400kg/ hour.

Self-contained Hopper Loader

1. Self-contained Hopper Loader Introduction

AUMAX AML-400G three phase combined vacuum hopper loader machine is special designed for conveying plastic resin materials in plastic injection molding industry. This vacuum auto loader equipped with three phase induction type air pump. The machine has reversal function to clean the dust on the filters. The capacity of AML-400G hopper loader is 300kg ~400kg/ hour.

2. Self-contained Hopper Loader Parameter (Specifications)

Model	Motor		Capacity (Kg/h)	Hopper Size (L)	Pipe diameter (mm)	Dimensions (mm)	Weight (Kg)
	Type	Power					
AML-400G	Carbon Brush	1.5HP/3Phase	400	8	Ø38	850x 450 x450	35

Please excuse for not note if some specifications of products are changed!

Note:

- 1) The test condition of conveying capacity: vertical distance 4 meters, horizontal distance 1 meter.
- 2) The standard power voltage for AML-400G is 3 phases, 380V, 50/60Hz. Other voltage such as 220V, 400V, 415V and 440V is available.

Ningbo Aumax Plastic Machinery Co., Ltd

Address: No. 216, Lianhe Rd., Ningbo Economic & Tech Development Zone, Beilun, Ningbo, China

Phone: +86-13819843291

Tel: +86-574-26850648

Fax: +86-574-26855258

E-mail: sales@aumax-plast.com

3. Self-contained Hopper Loader Features & Application

1. AML-400G Combined vacuum autoloader equipped with dust filter and dust collecting bag.
2. The hopper loader with automatic reversal clean function to clean filter.
3. Integrated structure for easy installation.
4. Machine equipped with wired remote control panel for easy operation and setting.
5. Vacuum hopper made of stainless steel to keep plastic resin without pollution.
6. Large power air pump ensures a big transportation and feeding capacity.

Packing:



Shipping:



Sea Transportation

Air Transportation

Express

4. FAQ

1. Q: What is the MOQ?

A: The MOQ is 1 set for all products..

2. Q: Where is the loading port?

A: The nearest port to our factory is port of Ningbo, China, as well as we can send machine to Yiwu, Shanghai, Guangdong or any other cities in China.

Ningbo Aumax Plastic Machinery Co., Ltd

Address: No. 216, Lianhe Rd., Ningbo Economic & Tech Development Zone, Beilun, Ningbo, China

Phone: +86-13819843291

Tel: +86-574-26850648

Fax: +86-574-26855258

E-mail: sales@aumax-plast.com



www.aumaxplast.com

3. Q: What are the payment terms?

A: The preferential payment term is T/T, while other payment terms are negotiable.

4. Q: What are your terms of delivery?

A: We accept FOB, CFR, CIF, EXW, and DDU. You can choose the terms which is the most convenient and cost effective to you.

5. Q: How does your factory carry out quality control?

A: Powerful R&D teams and professional QC department take care of every detail during design, processing, assembling, testing and packing.

6. Q: Can you supply OEM and customized products?

A: Yes, we can supply OEM / ODM service. Our engineers have rich experience in design and production of plastic auxiliary equipment. We can supply special products according to your ideas and drawings.

7. Q: What about warranty terms?

A: We provide one year warranty for all of our products. During warranty period, if any machine parts damaged due to quality, we will send the new parts by courier immediately by free of charge. Also, we supply 24 hours online service and technical support.

Ningbo Aumax Plastic Machinery Co., Ltd

Address: No. 216, Lianhe Rd., Ningbo Economic & Tech Development Zone, Beilun, Ningbo, China

Phone: +86-13819843291

Tel: +86-574-26850648

Fax: +86-574-26855258

E-mail: sales@aumax-plast.com