



Brass Hose Connector

As a result of our specialty and service consciousness, our company has won a good reputation among customers all over the world. The production of qualified JIXIANG CONNECTOR® Brass Hose Connector in the factory of JiXiang undergoes rigorous inspections. So we can guarantee that every product delivered to you must be of high quality. Our Brass Hose Connector are completely independently producing and supporting OEM/ODM orders. We have perfect after-sales service to ensure your satisfaction.

Product Description

These are related to the JIXIANG CONNECTOR® Brass Hose Connector news, in which you can learn about the updated information in Brass Hose Connector, to help you better understand and expand Brass Hose Connector market. Because the market for Brass Hose Connector is evolving and changing, so we recommend that you collect our website, and we will show you the latest news on a regular basis.

Buy Brass Hose Connector from China Suppliers

JIXIANG CONNECTOR® Brass Hose Connectors are mainly used for the connection of line protection line pipes and power distribution equipment in electrician and electrical, petrochemical, basic construction, power transmission and distribution systems and other industries; therefore, we must choose Brass Hose Connector with matching specifications.

Brass Hose Connector Parameter (Specification)

Brass Hose Connector								
Product Code	ΦI (mm)	Thread(mm)	Fits to Tubing size	ΦB(mm)	C (mm)	D (mm)	SW1	SW2
JX-M10-BH	6.5	M10*1.0	AD10	19	10	31	15	17
JX-M12-BH	9.0	M12*1.5	AD14	23	10	33	19	21
JX-M16-BH	12.5	M16*1.5	AD17	27	10	33	23	25
JX-M20-BH	16.0	M20*1.5	AD21	31	10	33	27	29

JX-M25-BH	21.0	M25*1.5	AD27	39	11	41	34	36
JX-M32-BH	27.5	M32*1.5	AD36	48	13	43	43	45
JX-M40-BH	35.5	M40*1.5	AD45	57	13	43	52	54
JX-M50-BH	45.5	M50*1.5	AD56	70	14	49	63	66
JX-M63-BH	49	M63*1.5	AD56	70	14	49	63	66
JX-PG7-BH	6.5	PG7	AD10	19	7	28	15	17
JX-PG9-BH	10.0	PG9	AD14	23	7	30	19	21
JX-PG11-BH	12.5	PG11	AD17	27	7	30	23	25
JX-PG13.5-BH	14.5	PG13.5	AD19	29	7	30	25	27
JX-PG16-BH	16.0	PG16	AD21	31	7	30	27	29
JX-PG21-BH	21.0	PG21	AD27	39	10	40	34	36
JX-PG29-BH	29.0	PG29	AD36	48	10	40	43	45
JX-PG36-BH	38.0	PG36	AD45	57	10	40	52	54
JX-PG48-BH	49.0	PG48	AD56	70	10	45	63	66

Brass Hose Connector Feature And Application

Application of Brass Hose Connector

1. The Brass, nickel plated connector body, which has strong flexibility, flexibility, bending resistance and vibration resistance. The strengthened protection of the woven mesh sleeve makes it have a higher pressure bearing capacity.
2. In addition to the thread and flange standards, the connection methods at both ends of the hose can also adopt other connection methods, which are convenient for connection and use.
3. Since both ends of the Brass hose connector are made of brass, nickel plated, it is not only suitable for matching with rotary joints, but also widely used in flexible connections to transport various fluid media.



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

Brass Hose Connector Details

Brass Hose Connector

Material: Brass / Brass with nickel Plated

Protection Degree: IP67

Thread Type: Metric, PG

Function: Connectors are mainly for SOR-PVC-AS, SPR-PUPAS, FLEXAgraff – PU-AS metal conduits. Can be used in flexible metallic conduit or liquid tight conduit in Power Plant, Power transmission system, communication system, building factory, railway, train, transportation system project, air conditioner, various machines, automates controlling plant. And it protects the electrical wire or cable outside the construction and plant.

Brass Hose Connector Qualification

Certificates of Brass Hose Connector: CE, IP68,ISO9001



Deliver,Shipping And Serving

Delivery of Brass Hose Connector Normally 7 working days to 1 month after received the payment.