





## **Brass Reducer**

ght from raw material to finished products, the emphasis on quality has been a pivotal pillar on which the brand Jixiang steadfastly rests.We have a complete and scientific quality management system for JIXIANG CONNECTOR® Brass Reducer.All your inquiries will be replied to in 24 hours. Reasonable quality and reasonable price you will get from us.

### **Product Description**

These are related to the JIXIANG CONNECTOR® Brass Reducer news, in which you can learn about the updated information in Brass Reducer, to help you better understand and expand Brass Reducer market. Because the market for Brass Reducer is evolving and changing, so we recommend that you collect our website, and we will show you the latest news on a regular basis.We have achieved remarkable success in this domain as a result of our focused approach, timely delivery, and ethical company philosophy.

# High Quality China Brass Reducer CE Factory

JIXIANG CONNECTOR® Brass Reducer can transform different threads OD freely; Change larger Thread to smaller Thread. The brass reducer have a plating that makes them shiny and improves corrosion resistance.

Brass Reducer - Size Chart										
Circle Series	Hexagon series	Item			Heig	Hexag				
		Male thread (D1)	Female thread (D2)	Inread	ht (H)m m	on size				
JX-M16/12A-RE	JX-M16/12B-RE	M16*1.5	M12*1.5	6	8.5	18				
JX-M20/16A-RE	JX-M20/16B-RE	M20*1.5	M16*1.5	6.5	9	24				
JX-M25/20A-RE	JX-M25/20B-RE	M25*1.5	M20*1.5	7.5	10	30				
JX-M32/25A-RE	JX-M32/25B-RE	M32*1.5	M25*1.5	8	11.5	40				

### **Brass Reducer Parameter (Specification)**



www.jxcablegland.com

JX-M40/32B-RE	M40*1.5	M32*1.5	9	12.5	43
JX-M50/40B-RE	M50*1.5	M40*1.5	10	14	57
JX-M63/50B-RE	M63*1.5	M50*1.5	10	14	64
JX-PG9/PG7B-RE	PG9	PG7	6	8.5	17
JX-PG11/PG9B-RE	PG11	PG9	6.5	8.5	20
JX-PG13.5/PG11B- RE	PG13.5	PG11	6.5	9	22
	PG16	PG13.5	6.5	9.5	24
JX-PG21/PG16B-R E	PG21	PG16	7.5	10	30
JX-PG29/PG21B-R E	PG29	PG21	8	11.5	40
JX-PG36/PG29B-R E	PG36	PG29	9	12.5	50
JX-PG42/PG36B-R E	PG42	PG36	10	14	57
JX-PG48/PG42B-R E	PG48	PG42	10	14	64
	NPT1/2"	NPT3/8"	6.5	9	24
JX-NPT3/4"-NPT1/ 2"B-RE	NPT3/4"	NPT1/2"	7.5	10	30
	NPT1"	NPT3/4"	8	11.5	40
JX-NPT1-1/4"-NPT 1"B-RE	NPT1-1/4"	NPT1"	9	12.5	50
	JX-M50/40B-RE JX-M63/50B-RE JX-PG9/PG7B-RE JX-PG11/PG9B-RE JX-PG13.5/PG11B- RE JX-PG16/PG13.5B- RE JX-PG29/PG21B-R E JX-PG29/PG21B-R E JX-PG36/PG29B-R E JX-PG42/PG36B-R E JX-PG42/PG36B-R E JX-PG48/PG42B-R E JX-NPT1/2"-NPT3/ 8"B-RE JX-NPT1/2"-NPT3/ 8"B-RE JX-NPT1/2"-NPT3/4"	JX-M50/40B-RE M50*1.5   JX-M63/50B-RE M63*1.5   JX-PG9/PG7B-RE PG9   JX-PG11/PG9B-RE PG11   JX-PG13.5/PG11B- PG13.5   RE PG16   JX-PG21/PG16B-R PG21   JX-PG29/PG21B-R PG29   JX-PG36/PG29B-R PG36   JX-PG42/PG36B-R PG42   JX-PG48/PG42B-R PG48   JX-NPT1/2"-NPT3// NPT1/2"   JX-NPT3/4"-NPT1/ NPT3/4"   JX-NPT1-1/4"-NPT NPT1-1/4"	JX-M50/40B-RE   M50*1.5   M40*1.5     JX-M63/50B-RE   M63*1.5   M50*1.5     JX-PG9/PG7B-RE   PG9   PG7     JX-PG11/PG9B-RE   PG11   PG9     JX-PG13.5/PG11B- RE   PG13.5   PG11     JX-PG16/PG13.5B- RE   PG16   PG13.5     JX-PG21/PG16B-R E   PG21   PG16     JX-PG29/PG21B-R E   PG29   PG21     JX-PG36/PG29B-R E   PG36   PG29     JX-PG42/PG36B-R E   PG42   PG36     JX-NPT1/2"-NPT3/ 8"B-RE   NPT1/2"   NPT3/8"     JX-NPT3/4"-NPT1/ 2"B-RE   NPT3/4"   NPT1/2"     JX-NPT1"-NPT3/4"   NPT1-1/4"   NPT3/4"	JX-M50/40B-RE   M50*1.5   M40*1.5   10     JX-M63/50B-RE   M63*1.5   M50*1.5   10     JX-PG9/PG7B-RE   PG9   PG7   6     JX-PG11/PG9B-RE   PG11   PG9   6.5     JX-PG13.5/PG11B-   PG13.5   PG11   6.5     JX-PG16/PG13.5B-   PG16   PG13.5   6.5     JX-PG21/PG16B-R   PG21   PG16   7.5     JX-PG29/PG21B-R   PG29   PG21   8     JX-PG42/PG36B-R   PG36   PG29   9     JX-PG42/PG36B-R   PG42   PG36   10     JX-PG48/PG42B-R   PG48   PG42   10     JX-NPT1/2"-NPT3/   NPT1/2"   NPT3/8"   6.5     JX-NPT3/4"-NPT1/   NPT3/4"   NPT1/2"   7.5	JX-M50/40B-RE   M50*1.5   M40*1.5   10   14     JX-M63/50B-RE   M63*1.5   M50*1.5   10   14     JX-PG9/PG7B-RE   PG9   PG7   6   8.5     JX-PG11/PG9B-RE   PG11   PG9   6.5   8.5     JX-PG13.5/PG11B-   PG13.5   PG11   6.5   9     JX-PG21/PG16B-R   PG21   PG16   7.5   10     JX-PG29/PG21B-R   PG29   PG21   8   11.5     JX-PG36/PG29B-R   PG36   PG29   9   12.5     JX-PG42/PG36B-R   PG42   PG36   10   14     JX-PG42/PG36B-R   PG48   PG42   10   14     JX-NPT1/2"-NPT3/   NPT1/2"   NPT3/8"   6.5   9     JX-NPT3/4"-NPT1/   NPT3/4"   NPT1/2"   7.5   10     JX-NPT3/4"-NPT1/   NPT3/4"   NPT3/4"   8   11.5     JX-NPT1-1/4"-NPT3/4"   NPT1-1/4"   NPT3/4"   8   11.5

### **Brass Reducer Feature And Application**

Function: Brass Reducer is used if the dimensions of existing tapped Holes are too large for a given gland. It provides a means of connection between cable entry devices and equipment having dissimilar Threads.



Yueqing Jixiang Connector Co., Ltd.







PHOTOVOLTAIC (PV)





WHEEL TRANSPORT DOCK

# **Brass Reducer Details**

## **Products:**

Material: Brass with nickel-plated Working Temperature: -40 deg to 100 deg, short time to 120 deg Shape: hexagonal or round Certificate: CE, IP68 Features: Brass Reducer can transform different threads OD freely; Change larger Thread to smaller Thread.

Function: Brass Reducer is used if the dimensions of existing tapped Holes are too large for a given gland. It provides a means of connection between cable entry devices and equipment having dissimilar Threads.

Accessories: Locknut, Sealing Washer

Note: We can produce different thread lengths of Brass Reducer and the other sides of threads (not standard) as the requirement of customer.



### Brass Reducer Qualification

Certificates of Brass Reducer: CE, IP68





#### **Deliver, Shipping And Serving**

Delivery of Brass reducer Normally 7 working days to 1 month after received the payment.

**Recommend Product** 

**Stainless Steel Reducer** 

JIXIANG CONNECTOR® Stainless steel reducer is designed for adjusting the different thread sizes, when the cable gland has a smaller thread size than the enclosure entry thread size, you must consider selecting a suitable cable gland reducer to connect them.





### **Brass Enlarger**

JIXIANG CONNECTOR® Brass Enlarger can transform different threads OD freely; Change smaller Thread to lager Thread.

