



Brass Standard Cable Gland PG Thread

We supply JIXIANG CONNECTOR® Brass standard cable gland PG Thread with TUV, ROHS, REACH, CE, etc approved.

Product Description

These are related to the JIXIANG CONNECTOR® Brass Standard Cable Gland PG Thread news, in which you can learn about the updated information in Brass Standard Cable Gland PG Thread, to help you better understand and expand Brass Standard Cable Gland PG Thread market. Because the market for Brass Standard Cable Gland PG Thread is evolving and changing, so we recommend that you collect our website, and we will show you the latest news on a regular basis.

China Brass Standard Cable Gland PG Thread IP68 Price

JIXIANG CONNECTOR® Brass standard cable gland PG Thread may be used on all types of electrical power, control, instrumentation, data and telecommunications cables. They are used as a sealing and termination device to ensure that the characteristics of the enclosure which the cable enters can be maintained adequately.

Brass Standard Cable Gland PG Thread Parameter (Specification)

Metal cable gland - PG thread series							
Product Code	Thread specification AG	Available cable range(mm)	Thread O.D (mm)	Mounting Hole Diamter (mm)	Thread Length GL(mm)	Joint Length H(mm)	Spanner size (mm)
JX-PG7-NP	PG7	6.5-3	12.5	12.5-12.7	7	19	14
JX-PG9-NP	PG9	8-4	15.2	15.2-15.4	8	20	18
JX-PG11-NP	PG11	10-5	18.6	18.6-18.8	8	21	20

JX-PG13.5-NP	PG13.5	12-6	20.4	20.4-20.6	8	22	22
JX-PG16-NP	PG16	14-10	22.5	22.5-22.7	9	23	24
JX-PG19A-NP	PG19	14-10	25	25-25.2	9	25	24/27
JX-PG19B-NP	PG19	16-8	25	25-25.2	9	25	27
JX-PG21A-NP	PG21	18-13	28.3	28.3-28.5	9	27	30/32
JX-PG21B-NP	PG21	16-9	28.3	28.3-28.5	9	27	30/32
JX-PG25-NP	PG25	22-15	32	32-32.2	10	29	35
JX-PG29-NP	PG29	25-18	37	37-37.2	11	31	40
JX-PG36-NP	PG36	33-25	47	47-47.2	12	37	50
JX-PG42-NP	PG42	38-32	54	54-54.2	13	38	57
JX-PG48-NP	PG48	44-37	59.3	59.3-59.5	14	38	64
JX-PG63NP	PG63	52-42	72	72-72.2	15	42	78

Brass Standard Cable Gland PG Thread Feature And Application

Features: The Brass standard cable gland PG Thread is a product of large scope, high tensile strength, waterproof, dustproof, salt, acid and alkali resistance, alcohol, oil and solvent resistance.

Function: Brass standard cable gland PG Thread is the product forms a complete set of the cable, connector cable can be locked, and the other end can access the devices through the box body, also can choose thread access according to the entry and outlet of the internal thread electric devices.

More options: Customization is acceptable. Welcome to inquire



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

Brass Standard Cable Gland PG Thread Details

Thread specification: PG

Product material: The Brass standard cable gland PG Thread body parts are made of brass, the clamping part is made of nylon (PA), and the seals and O-ring are made of nitride rubber (NBR).

Certificates: CE, ROHS, IP68, ISO9001, TUV

Protection Degree: In the specific cable range, the using of O-ring helps tighten head so that to reach IP68-10 bar.

Working Temperature: : -40°C to 100 °C, short time of up to 120°C. Dynamic: - 20 °C to 80 °C, short time of up to 100 °C

Thread Length: The short thread suitable for holes in thin board or equipment with inner thread, while the long thread is available for thick plate. Threaded extension can be

customized.

Brass Standard Cable Gland PG Thread Qualification

Certificates of Brass standard cable gland PG Thread CE,ROHS, REACH, IP68,ISO9001,TUV



Deliver,Shipping And Serving

Delivery of Brass standard cable gland PG Thread Normally 7 working days to 1 month after received the payment.

Related Products

[Nylon Cable Gland](#)

Nylon Cable Gland are defined as 'mechanical cable entry devices' which are used in conjunction with cable and wiring for electrical, instrumentation & control, and automation systems, including lighting, power, data and telecoms.



Stainless Steel Cable Gland

Stainless steel cable glands are a connection device often used in power systems. Mainly suitable for outdoor products, medium and large remote control machinery, and some equipment whose main body is in the outdoor control system but not on the main body.

