



Brass Through Type Cable Gland Metric Thread



Our JIXIANG CONNECTOR® Brass through type cable gland Metric Thread can be used in many fields, such as energy generation, rail transit, new energy vehicles, charging station systems, power electronic systems, heavy industry systems, etc. The Brass through type cable gland Metric Thread quality is reliable, safe and environmentally friendly. Basically, glands will be connected to panels, distribution boxes and electric

equipments, etc. Simply message us with your requirements and we will get back to you ASAP with a quote!

Product Description

These are related to the JIXIANG CONNECTOR® Brass Through Type Cable Gland Metric Thread news, in which you can learn about the updated information in Brass Through Type Cable Gland Metric Thread, to help you better understand and expand Brass Through Type Cable Gland Metric Thread market. Because the market for Brass Through Type Cable Gland Metric Thread is evolving and changing, so we recommend that you collect our website, and we will show you the latest news on a regular basis.

Brass Through Type Cable Gland Metric Thread IP68

JIXIANG CONNECTOR® Brass through type cable gland Metric Thread may be used on all types of electrical power, control, instrumentation, data and telecommunications cables.

They are used as a sealing and termination device to ensure that the characteristics of the enclosure which the cable enters can be maintained adequately.

Brass Through Type Cable Gland Metric Thread Parameter (Specification)

Brass Through Type Cable Gland Metric Thread Size Chart						
Product Code	Thread specification AG	Available cable range (mm)	Thread O.D. (mm)	Mounting Hole Diameter (mm)	Thread length GL (mm)	Spanner Size (mm)
JX-M12-TR	M12*1.5	6.5-3	12	12.12.2	7	14

JX-M14-TR	M14*1.5	6.5-3	14	14-14.2	7	17
JX-M16-TR	M16*1.5	8-4	16	16-16.2	7	18
JX-M18-TR	M18*1.5	10-5	18	18-18.2	8	20
JX-M20-TR	M20*1.5	12-6	20	20-20.2	8	22
JX-M22-TR	M22*1.5	14-10	22	22-22.2	8	24
JX-M27A-TR	M27*1.5	18-13	27	27-27.2	9	30
JX-M27B-TR	M27*2	18-13	27	27-27.2	9	30
JX-M28A-TR	M28*1.5	18-13	28	28-28.2	9	30
JX-M28B-TR	M28*2	18-13	28	28-28.2	9	30
JX-M30A-TR	M30*1.5	18-13	30	30-30.2	9	30/32
JX-M30B-TR	M30*2	18-13	30	30-30.2	9	30/32
JX-M32A-TR	M32*1.5	22-15	32	32-32.2	10	35
JX-M32B-TR	M32*2	22-15	32	32-32.2	10	35
JX-M33A-TR	M33*1.5	22-15	33	33-33.2	10	35
JX-M33B-TR	M33*2	22-15	33	33-33.2	10	35
JX-M37A-TR	M37*1.5	25-18	37	37-37.2	10	40
JX-M37B-TR	M37*2	25-18	37	37-37.2	10	40
JX-M40A-TR	M40*1.5	25-18	40	40-40.2	11	40/45
JX-M40B-TR	M40*2	25-18	40	40-40.2	11	40/45
JX-M47A-TR	M47*1.5	33-25	47	47-47.2	11	50
JX-M47B-TR	M47*2	33-25	47	47-47.2	11	50
JX-M48A-TR	M48*1.5	33-25	48	48-48.2	11	50/52
JX-M48B-TR	M48*2	38-32	48	48-48.2	11	50/52
JX-M54A-TR	M54*1.5	38-32	54	54-54.2	12	57
JX-M54B-TR	M54*2	38-32	54	54-54.2	12	57
JX-M56A-TR	M56*1.5	38-32	56	56-56.2	12	57/59
JX-M56B-TR	M56*2	38-32	56	56-56.2	12	57/59
JX-M60A-TR	M60*1.5	44-37	60	60-60.2	13	64

JX-M60B-TR	M60*2	44-37	60	60-60.2	13	64
JX-M63A-TR	M63*1.5	44-37	63	63-63.2	13	64/68
JX-M63B-TR	M63*2	44-37	63	63-63.2	13	64/68
JX-M64A-TR	M64*1.5	44-37	64	64-64.2	13	64/68
JX-M64B-TR	M64*2	44-37	64	64-64.2	13	64/68

Brass Through Type Cable Gland Metric Thread Feature And Application

Features: The Brass through type cable gland Metric Thread is a product of large range, high tensile strength, waterproof, dustproof, salt, acid, alcohol, grease and common solvent resistant.

Function: Brass through type cable gland Metric Thread is cable supporting products, connector cable can be locked, the other end of the device can access the devices through the box body, also can choose thread access according to the entry and outlet of the internal thread electrical equipment.

More options: Customization of Brass through type cable gland Metric Thread is acceptable. Welcome to inquire when ordering.



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW EN



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TR

Brass Through Type Cable Gland Metric Thread Details

Products:

Thread Size: Metric Thread

Material: The joint body parts are made of nickel plated brass, the clamping part is made of plastic(PA), and the seals and O-ring seals are made of nitrile rubber (NBR).

Operating temperature: Static: -40 °C to 100 °C, short time up to 120 °C. Dynamic: -20 °C to 80 °C, short time up to 100 °C

Thread length: The short thin thread is suitable for holes in thin board or devices with internal thread, while the long thread is available for thick board. Long threads can be customized.

Brass Through Type Cable Gland Metric Thread Qualification

Certificates of Brass through type cable gland Metric Thread: CE,ROHS, REACH, IP68,ISO9001



Deliver,Shipping And Serving of Brass Through Type Cable Gland Metric Thread

Delivery of Brass through type cable gland Metric Thread Normally 7 working days to 1 month after received the payment.

Products Recommend

[Nylon Standard Cable Gland Metric Thread](#)

JIXIANG CONNECTOR® Nylon standard cable gland Metric Thread is IP68 rated protection that withstands dust, dirt and sand etc, and protect precious electrical connections and safeguard your electrical project with commercial grade strain relief.



[Stainless Steel Cable Glands Metric Thread](#)

JIXIANG CONNECTOR® Stainless steel cable glands Metric Thread is a kind of connection device often used in power system.

