



Cable Gland Nickel Plated Brass

We have rich experience and strong strength and are recognized and loved by customers for JIXIANG CONNECTOR® Cable Gland Nickel Plated Brass all over the world. We independently produce and design many types of #CablbeGlands and #CableConnectors, which can meet your various needs. Say Cable Gland Nickel Plated Brass. More designs are welcome to communicate with us. We have strong R&D

capabilities and can provide you with OEM&ODM services for Cable Gland Nickel Plated Brass.

Product Description

With years of experience in production JIXIANG CONNECTOR® Cable Gland Nickel Plated Brass, Yueqing Jixiang Connector Co., Ltd. can supply a wide range of Cable Gland Nickel Plated Brass. High quality Cable Gland Nickel Plated Brass can meet many applications, if you need, please get our online timely service about Cable Gland Nickel Plated Brass. In addition to the product list below, you can also customize your own unique Cable Gland Nickel Plated Brass according to your specific needs. Sincerely look forward to cooperating with you in the near future.

Cable Gland Nickel Plated Brass Suppliers from China

JIXIANG CONNECTOR® Cable Gland Nickel Plated Brass may be used on all types of electrical power, control, instrumentation, data and telecommunications cables.

They are used as a sealing and termination device to ensure that the characteristics of the enclosure which the cable enters can be maintained adequately.

Parameter (Specification) of Cable Gland Nickel Plated Brass

Brass Cable Gland - Metric thread							
Product Code	Thread AG	Applicable cable range(mm)	Thread O.D.(mm)	Mounting Hole Diameter (mm)	Thread length GL(mm)	Spanner Size (mm)	Std, Pkg (pcs)
JX-M12A-MG	M12x1.5	3-5.3	12	12-12.3	8	17/17	10

JX-M12B-MG		4.5-7.8	12	12-12.3	8	17/17	10
JX-M16A-MG	M16×1.5	4-7	16	16-16.3	9	22/22	10
JX-M16B-MG		6-10	16	16-16.3	9	22/22	10
JX-M20A-MG	M20×1.5	5-8.8	20	20-20.3	9.5	24/24	10
JX-M20B- MG		7-12	20	20-20.3	9.5	24/24	10
JX-M20C- MG		9-14	20	20-20.3	9.5	26/26	10
JX-M25- MG	M25×1.5	14-18	25	25-25.4	12	32/32	10
JX-M32A- MG	M32×1.5	16-22	32	32-32.4	12.5	41/41	10
JX-M32B- MG		18-25	32	32-32.4	12.5	41/41	10
JX-M40A- MG	M40×1.5	21-25	40	40-40.4	15	50/50	10
JX-M40B- MG		24-30	40	40-40.4	15	50/50	5
JX-M50A- MG	M50×1.5	26-32	50	50-50.4	15	60/60	2
JX-M50B- MG		31-41	50	50-50.4	15	60/60	2
JX-M63- MG	M63×1.5	44-37	63	63-63.4	15	73/73	2

More options: Customization of Cable Gland Nickel Plated Brass is acceptable. Welcome to inquire.

Feature And Application of Cable Gland Nickel Plated Brass

Features: The claws and seals of excellent design, sealing nut have a “click” sound and re-open, can hold cable firmly and have a wider cable range. Resistant to salt water, weak acid, alcohol, oil, grease and common solvency.

Function: Cable Gland Nickel Plated Brass is cable supporting products, connector cable can be locked, the other end of the device can access the device through the box body, also can choose thread access according to the entry and outlet of the internal thread electrical equipment.



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

Details of Cable Gland Nickel Plated Brass

Connection Thread: Metric

Material:

Cap nut: Brass with nickel Plated

Clamping Insert: PA66

Sealing Ring: EPDM

Gland Body: Brass with nickel plated

Certificate: CE, IP68, ISO9001

Protection Class : IP68-10 BAR

Operating Temperature: -40 °C to +100 °C, (short time to 120 °C); -20 °C to 80 °C, (short time to 100 °C)

Qualification of Cable Gland Nickel Plated Brass

Certificates of Cable Gland Nickel Plated Brass: CE,ROHS, REACH, IP68,ISO9001



Deliver,Shipping And Serving

Delivery of Cable Gland Nickel Plated Brass Normally 7 working days to 1 month after received the payment.