

## **Elbow Brass Waterproof Cable Gland**

Elbow Brass Waterproof Cable Gland are used to protect and anchors cable at chassis entry, protects from water & dust and is suitable for various outdoor applications.Jixiang Connector Brass Waterproof Cable Gland are made of high quality brass, smooth surface, no burrs, longer life span with best functional outcome and for it's application in various industries.

### **Product Description**

Yueqing Jixiang Connector Co., Ltd. is a professional China Elbow Brass Waterproof Cable Gland manufacturer and supplier, if you are looking for the best Elbow Brass Waterproof Cable Gland with low price, consult us now! We have the distinct advantage that each and every employee is personally responsible for the company's success. Everything we do is infused with pride of ownership and pride in a job well done.

# Customized Wholesale Elbow Brass Waterproof Cable Gland CE Price Manufactuerers

## What is Elbow Brass Waterproof Cable Gland

JIXIANG CONNECTOR® Elbow Brass Waterproof Cable Gland may be used on all types of electrical power, control, instrumentation, data and telecommunications cables. Elbow Brass Waterproof Cable Gland are used to protect and anchors cable at chassis entry, protects from water & dust and is suitable for various outdoor applications.

JIXIANG CONNECTOR® Elbow Brass Waterproof Cable Gland are made of high quality brass, smooth surface, no burrs, longer life span with best functional outcome and for it's application in various industries.

Elbow Brass Waterproof Cable Gland Size Chart							
Product	Code	Thread O D		U	0	Spanner Size (mm)	

## Elbow Brass Waterproof Cable Gland Parameter (Specification)



Yueqing Jixiang Connector Co., Ltd.

www.jxcablegland.com

		1 0 0			9
JX-M12-6.5-9D	12	3-6.5	45	9	20/21
JX-M16-6.5-9D	16	3-6.5	45	9	20/21
JX-M16-8-9D	16	4-8	45	9	20/21
JX-M16-10-9D	16	5-10	57	10	20/25
JX-M18-10-9D	18	5-10	57	10	20/25
JX-M20-10-9D	20	5-10	57	10	24/25
JX-M20-12-9D	20	6-12	57	10	24/30
JX-M20-14-9D	20	8-14	58	15	24/30
JX-M22-14-9D	22	8-14	58	15	24/30
JX-M24-12-9D	24	6-12	58	15	24/30
JX-M24-14-9D	24	8-14	58	15	24/30
JX-M25-14-9D	25	8-14	58	15	28/34
JX-M25-16-9D	25	10-16	75	15	30/34
JX-M25-18-9D	25	13-18	75	15	28/34
JX-M27-16-9D	27	10-16	75	15	30/34
JX-M27-18-9D	27	13-18	75	15	28/34
JX-M30-16-9D	30	10-16	75	15	30/34
JX-M30-18-9D	30	13-18	75	15	30/34
JX-M32-18-9D	32	13-18	75	15	30/34
JX-M32-22-9D	32	15-22	75	15	30/43
JX-M32-25-9D	32	18-25	90	15	40/43
JX-M33-25-9D	33	18-25	90	15	40/43
JX-M36-22-9D	36	15-22	90	15	36/43
JX-M36-25-9D	36	18-25	90	15	40/43
JX-M40-25-9D	40	18-25	90	15	40/43
JX-M40-30-9D	40	22-30	105	15	50/55
JX-M40-32-9D	40	22-32	115	15	50/55
JX-M42-32-9D	42	22-32	115	15	50/55



Yueqing Jixiang Connector Co., Ltd.

www.jxcablegland.com

JX-M48-32-9D	48	22-32	115	15	50/55
JX-M50-38-9D	50	30-38	115	15	55/60
JX-M56-38-9D	56	30-38	115	15	55/60
JX-M60-44-9D	60	37-44	125	18	65/70
JX-M63-44-9D	63	37-44	125	18	75/75
JX-M64-44-9D	64	37-44	125	18	65/70

## Elbow Brass Waterproof Cable Gland Feature And Application

Function: Elbow Brass Waterproof Cable Gland can be used in flexible metallic conduit or liquid tight conduit in Power Plant, Power transmission system, communication system, building factory, railway, train, transportation system project, air conditioner, various machines, automates controlling plant. And protecting the electrical wire or cable outside the construction and plant. Elbow Brass Waterproof Cable Gland can be used in flexible metallic conduit or liquid tight conduit in Power plant, Power transmission system, communicationsystem, building factory, railway, train, transport plant, Power transmission system, communicationsystem, building factory, railway, train, trans portation system project etc.

Jixiang Connector Elbow Brass Waterproof Cable Gland offer good strain relief with the wide clamping range and screwed tightly on the cable assembly to provide high strength connection and installation.

## Featurers of Elbow Brass Waterproof Cable Gland

Good performance in strain relief Oil and Chemical Resistant Protects against ingress of water and dust Portects and anchors cable at chassis entry For application in installation areas with small amounts of space due to construction dimensions





PHOTOVOLTAIC (PV)

OUTDOOR ADVERTISEMENTS

WHEEL TRANSPORT DOCK

## Elbow Brass Waterproof Cable Gland Details

Products: Elbow Brass Waterproof Cable Gland Thread Size: Metric Thread Material: Body: brass nickel-plated Cap nut: brass nickel-plated Clamping Insert: PA6 Sealing ring: NBR ring: NBR Product Certification: CE certification and ISO9001. Working temperature: -40 °C to 100 °C, short time up to 120 °C.

## Elbow Brass Waterproof Cable Gland Qualification



Yueqing Jixiang Connector Co., Ltd.

Certificates of Elbow Brass Waterproof Cable Gland: CE, IP68, ISO9001





## **Deliver, Shipping And Serving**

Delivery of Elbow Brass Waterproof Cable Gland Normally 7 working days to 1 month after received the payment.

### **Cable Glands Recommend**

#### **Brass Flexible Cable Gland**

JIXIANG CONNECTOR® Brass flexible cable gland may be used on all types of electrical power, control, instrumentation, data and telecommunications cables.



Tel: +86-18958708338