



EMC Cable Gland D Series Metric Thread



As a manufacturing company that has a very strong focus on JIXIANG CONNECTOR® EMC Cable Gland D Series Metric Thread. This gives us a good reputation and makes our partners happy and satisfied. We have the perfect assembly line to produce high-quality EMC cable gland D series Metric Thread. We know what you need, we will solve your issues. You can trust us, satisfaction is our motto.

Product Description

Yueqing Jixiang Connector Co., Ltd. is EMC Cable Gland D Series Metric Thread manufacturers and suppliers in China who can wholesale EMC Cable Gland D Series Metric Thread. We can provide professional service and better price for you. If you interested in EMC Cable Gland D Series Metric Thread products, please contact with us. We follow the quality of rest assured that the price of conscience, dedicated service.

China EMC Cable Gland D Series Metric Thread Factory

JIXIANG CONNECTOR® EMC cable gland D series Metric Thread are used in various applications that need shielded cables for electromagnetic protection. Such EMC cable gland D series help in keeping the electromagnetic integrity of the protected cable. It is done by compressing the gland. It also offers an IP68 protection level and strain relief to the cable.

EMC Cable Gland D Series Metric Thread Parameter (Specification)

EMC cable gland D series Metric Thread							
Product Code	Thread A G	Cable range(m m)	Thread diameter(m m)	Board caliber(m m)	Thread length GL(mm)	Joint length(m m)	Wrench diameter (mm)
JX-D.M12-EMC	M12*1.5	6.5-3	12	12-12.2	7	19	14
JX-D.M14-EMC	M14*1.5	8-4	14	14-14.2	7	19	17
JX-D.M16-EMC	M16*1.5	8-4	16	16-16.2	8	20	18

JX-D.M18-EMC	M18*1.5	10-5	18	18-18.2	8	21	20
JX-D.M20-EMC	M20*1.5	12-6	20	20-20.2	8	22	22
JX-D.M22-EMC	M22*1.5	14-10	22	22-22.2	8	23	24
JX-D.M24-EMC	M24*1.5	14-10	24	24-24.2	9	25	24/27
JX-D.M25A-EMC	M25*1.5	14-10	25	25-25.2	9	25	24/27
JX-D.M25B-EMC	M25*1.5	18-13	25	25-25.2	9	27	30/27
JX-D.M27A-EMC	M27*1.5	18-13	27	27-27.2	9	27	30
JX-D.M27B-EMC	M27*2	18-13	27	27-27.2	9	27	30
JX-D.M28A-EMC	M28*1.5	18-13	28	28-28.2	9	27	30
JX-D.M28B-EMC	M28*2	18-13	28	28-28.2	9	27	30
JX-D.M30A-EMC	M30*1.5	18-13	30	30-30.2	9	29	30/32
JX-D.M30B-EMC	M30*2	18-13	30	30-30.2	9	29	30/32
JX-D.M32A-EMC	M32*1.5	22-15	32	32-32.2	10	29	35
JX-D.M32B-EMC	M32*2	22-15	32	32-32.2	10	29	35
JX-D.M33A-EMC	M33*1.5	22-15	33	33-33.2	10	29	35
JX-D.M33B-EMC	M33*2	22-15	33	33-33.2	10	29	35
JX-D.M36A-EMC	M36*1.5	25-18	36	36-36.2	10	31	40
JX-D.M36B-EMC	M36*2	25-18	36	36-36.2	10	31	40
JX-D.M37A-EMC	M37*1.5	25-18	37	37-37.2	10	31	40

JX-D.M37B-EM C	M37*2	25-18	37	37-37.2	10	31	40
JX-D.M40A-EM C	M40*1.5	25-18	40	40-40.2	11	31	40/45
JX-D.M40B-EM C	M40*2	25-18	40	40-40.2	11	31	40/45
JX-D.M40C-EM C	M40*1.5	30-22	40	40-40.2	11	35	45
JX-D.M40D-EM C	M40*2	30-22	40	40-40.2	11	35	45
JX-D.M42A-EM C	M42*1.5	30-22	42	42-42.2	11	35	45
JX-D.M42B-EM C	M42*2	30-22	42	42-42.2	11	35	45
JX-D.M47A-EM C	M47*1.5	33-25	47	47-47.2	11	37	50
JX-D.M47B-EM C	M47*2	33-25	47	47-47.2	11	37	50
JX-D.M48A-EM C	M48*1.5	33-25	48	48-48.2	11	37	50/52
JX-D.M48B-EM C	M48*2	33-25	48	48-48.2	11	37	50/52
JX-D.M50A-EM C	M50*1.5	38-32	50	50-50.2	12	37	50/55
JX-D.M50B-EM C	M50*2	38-32	50	50-50.2	12	37	50/55
JX-D.M54A-EM C	M54*1.5	38-32	54	54-54.2	12	38	57
JX-D.M54B-EM C	M54*2	38-32	54	54-54.2	12	38	57
JX-D.M56A-EM C	M56*1.5	38-32	56	56-56.2	12	38	57/59
JX-D.M56B-EM C	M56*2	38-32	56	56-56.2	12	38	57/59

JX-D.M60A-EMC	M60*1.5	44-37	60	60-60.2	13	38	64
JX-D.M60B-EMC	M60*2	44-37	60	60-60.2	13	38	64
JX-D.M63A-EMC	M63*1.5	44-37	63	63-63.2	13	38	64/68
JX-D.M63B-EMC	M63*2	44-37	63	63-63.2	13	38	64/68
JX-D.M64A-EMC	M64*1.5	44-37	64	64-64.2	13	38	64/68
JX-D.M64B-EMC	M64*2	44-37	64	64-64.2	13	38	64/68
JX-D.M72-EMC	M72*2	52-42	72	72-72.2	15	42	65/68
JX-D.M75-EMC	M75*2	52-42	75	75-75.2	15	42	78
JX-D.M80-EMC	M80*2	62-50	80	80-80.2	15	45	86/88
JX-D.M88-EMC	M88*2	70-60	88	88-88.2	15	45	98
JX-D.M100-EMC	M100*2	80-70	100	100-100.2	15	45	110

EMC Cable Gland D Series Metric Thread Feature And Application

JIXIANG CONNECTOR® EMC cable gland D series Metric Thread is a kind of specially designed metal cable gland which is used as an end. When shielded cable entries through this cable gland, the brass material contact chips attached in the cable gland will contact with the metal isolated network in the cable, Then the interfering electromagnetic wave will be leaded to the grounding wire, thus the interference source of electromagnetic wave will be evacuated. The brass materials EMC cable gland D series with different sizes are widely applicable for outlet areas when anti-electromagnetic is needed. It is also waterproof with IP68 protection degree.



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

EMC Cable Gland D Series Metric Thread Details

Thread Size: Metric Thread

Material: The EMC cable gland D series Metric Thread body parts are made of nickel plated brass, the clamping parts are made of plastic (PA) , and the seals and O-ring are made of nitrile rubber (NBR) .

Product Certification: CE, ROHS ,IP68 and ISO9001.

Protection Degree: in the specific cable range, the using of the O-ring helps tighten head, so that to reach IP68-10 bar pressure.

Working temperature: Static: -40 °C to 100 °C , short time up to 120 °C . Dynamic: -20 °C to 80 °C , short time up to 100 °C

Thread length: The short thread of EMC cable gland D series Metric Thread is suitable for holes in the board or equipment with inner thread, while the long thread is available for thick plated. Threads extension can be customized.

EMC Cable Gland D Series Metric Thread Qualification

Certificates of EMC cable gland D series Metric Thread: CE,ROHS, IP68,ISO9001



Deliver,Shipping And Serving

Delivery of EMC cable gland D series Metric Thread Normally 7 working days to 1 month after received the payment.