



## IP68 Gland



As the professional manufacture, we would like to provide you high quality JIXIANG CONNECTOR® IP68 Gland. And we will offer you the best after-sale service and timely delivery. At Jixiang we have since inception set the highest and remarkable benchmarks concerning product quality, product innovation and value engineering in the IP68 Gland. The commitment and consistency have helped us reach a level that our

product quality can easily match international standards.

### Product Description

The following is the introduction of high quality JIXIANG CONNECTOR® IP68 Gland, hoping to help you better understand IP68 Gland. Welcome new and old customers to continue to cooperate with us to create a better future! The company has always been oriented by customer demand and respect for talents, constantly improve their strength, improve service level and quality. With many European and American, Asian and domestic customers, we have established long-term good relationship with common progress. Sincerely expect to join hands with you to create the future.

### China IP68 Gland Size Chart

JIXIANG CONNECTOR® IP68 Gland may be used on all types of electrical power, control, instrumentation, data and telecommunications cables.

They are used as a sealing and termination device to ensure that the characteristics of the enclosure which the cable enters can be maintained adequately.

### IP68 Gland Parameter (Specification)

Cable Gland Size Chart - Metric Type					
Product Code	Thread AG	Cable range (mm)	Thread O.D.(mm)	Thread length GL(mm)	Spanner Size (mm)
JX-M8L	M8x1.0	2-5	8	8	12
JX-M10L	M10x1.0	3-6.5	10	10	14
JX-M12L	M12x1.5	3-6.5	12	10	14

JX-M14L	M14×1.5	4-8	14	12	17
JX-M16L	M16×1.5	4-8	16	12	18
JX-M18L	M18×1.5	5-10	18	12	20
JX-M20L	M20×1.5	6-12	20	12	22
JX-M22L	M22×1.5	10-14	22	12	24
JX-M24L	M24×1.5	10-14	24	12	24/27
JX-M25-14L	M25×1.5	10-14	25	12	24/27
JX-M25-18L	M25×1.5	13-18	25	12	30/27
JX-M27L	M27×1.5	13-18	27	12	30
JX-M28L	M28×1.5	13-18	28	12	30
JX-M30L	M30×1.5	13-18	30	14	30/32
JX-M32L	M32×1.5	15-22	32	14	35
JX-M33L	M33×1.5	15-22	33	14	35
JX-M36L	M36×1.5	18-25	36	14	40
JX-M37L	M37×1.5	18-25	37	14	40
JX-M40-25L	M40×1.5	18-25	40	15	40/45
JX-M40-30L	M40×1.5	22-30	40	15	45
JX-M42L	M42×1.5	22-30	42	15	45
JX-M47L	M47×1.5	25-33	47	15	50
JX-M48L	M48×1.5	25-33	48	15	50/52
JX-M50L	M50×1.5	32-38	50	15	57/55
JX-M54L	M54×1.5	32-38	54	15	57
JX-M60L	M60×1.5	37-44	60	16	64
JX-M63L	M63×1.5	37-44	63	16	64/68
JX-M64L	M64×2.0	37-44	64	16	64/68
JX-M72L	M72×2.0	42-52	72	18	78
JX-M75L	M75×2.0	42-52	75	18	78/80
JX-M80L	M80×2.0	50-62	80	20	86/88

JX-M88L	M88x2.0	60-70	88	20	98
JX-M100L	M100x2.0	78-84	100	22	110

### IP68 Gland Feature And Application

Function: Extremely easy installation, simply insert cable through the assembled gland and tighten gland locknut until cable is secured.

These JIXIANG CONNECTOR® IP68 Gland are designed to withstand water, dust, salt, acid-based, alcohol, oil and common solvent.

More options: Customization is acceptable. Welcome to inquire.



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

### IP68 Gland Details

Thread Size: Metric Thread

Tel: +86-18958708338

E-mail: [jx5@jxljq.net](mailto:jx5@jxljq.net)

Material: Brass with nickel plated

Claw: PA

Sealing and sealing ring: NBR

Product Certification: CE certification, TUV and ISO9001.

Patent: National Utility Model Patent No is ZL201020530888.7

Protection Degree: IP68

Working temperature: -40 °C to 100 °C short time to 120 °C

Thread Length: Longer thread waterproof cable gland is used for the thick board. Longer thread type can be produced as your requests.

### IP68 Gland Qualification

Certificates of IP68 Gland: CE, IP68, ISO9001



### Deliver, Shipping And Serving

Delivery of IP68 Gland: Normally 7 working days to 1 month after received the payment.