



IP68 Waterproof Cable Connector

Jixiang's IP68 Waterproof Cable Connector are an ideal accessory when you want fast connect the outdoor lighting and external wiring. Suitable for fast connection to the outdoor lighting, underfloor heating, beacon, watering cart, solar photovaltaic, cruise, etc.

Product Description

You are welcomed to come to our factory to buy the latest selling, low price, and high-quality JIXIANG CONNECTOR® IP68 Waterproof Cable Connector. We look forward to cooperating with you.We have achieved remarkable success in this domain as a result of our focused approach, timely delivery, and ethical company philosophy.

Plastic PA66 IP68 Waterproof Cable Connector

IP68 Waterproof Cable Connector Cable Gland Introduction

JIXIANG CONNECTOR'S IP68 Waterproof Cable Connector allows for the easy extension of wires, offer many of the benefits that conventional metal circular connectors do not.

Jixiang Connector is a professional manufacturer from China, whitch supply high quality IP68 Waterproof Cable Connector is made from durable plastic and copper alloy and will withstand all of the outdoor elements.

What is PA66:

PA66 is a dyadic nylon we can produce by high-temperature melt polymerization of adipic acid and hexamethylenediamine.

High strength and stiffness at high temperature and good abrasion and wear resistance That's why IP68 Waterproof Cable Connector are widely used in many different markets and applications due to their excellent performance/ cost ratios.

The Drawing of IP68 Waterproof Cable Connector:





IP68 Waterproof Cable Connector Parameter (Specification)

Size Chart

| Model Size | Cores | Voltage | Current | Cross Section | Cable Range | Length |
|------------|--------|---------|---------|-----------------------------|-------------|---------|
| M16 | 2P/3P | 400V | 7.5A | 0.5~1.5 mm ² | 3~6.5 mm | / |
| | | | | | 7~10 mm | |
| M20 | 2P/3P | 400V | 24A | 0.5~2.5 mm ² | 5~8 mm | 87.7 mm |
| | | | | 0.3~1.5 mm ² | 9~12mm | |
| M25 | 2P/3P/ | 400V | 24A | 2P/3P/4P: | 5~8 mm | 100 mm |
| | 4P/5P | | | 0.5~2.5 mm ² | 9~12 mm | |
| | | | | 5P: 0.5~2.5 mm ² | 10~14 mm | |
| M25-T | 2P/3P | 400V | 24A | 0.5~6.0 mm ² | 5~9 mm | 100 mm |
| | | | | | 9~12 mm | |
| | | | | | 10~14 mm | |

More options: Customization of PA66 Cable Gland is acceptable. Welcome to inquire.

Feature And Application of IP68 Waterproof Cable Connector

Tel: +86-18958708338 **E-mail:** jx5@jxljq.net



Our PA66 Cable Gland provide the highest degrees of functionality and safety. Features as bleow:

Made from Nylon PA66 can resistant to Salt water, gasoline, alcohol, oil, grease, easter keyton ether, benzine, common solvent, weak acids & weak alkalies.

High Protection IP68

Sample Installation, Plug and play

Strong electrical conductivity

Widely Application: Base station equipment, outdoor lamps, solar energy industry,

high-power energy storage equipment, etc



TERMINAL BOX

DISTRIBUTION BOX

NEW ENERGY VEHICLE



PHOTOVOLTAIC(PV)

THE SHIP

OUTDOOR LAMPS

The Details of IP68 Waterproof Cable Connector

Thread Specification: Metric Thread

Material: The PA66 Cable Gland dbody parts are made of PA66.

Rubber is EPDM.

Working Temperature:-40°C ~ +105°C

Connector type:Screw/Clip Wiring Gauge:0.5 - 2.5mm2 Voltage and Current rating:

400V / 17.5A

Protection level: IP 68-10 bar, waterproof, self-locking.
Colours: Black, White, other color available upon request



IP68 Waterproof Connector has prominent characteristics of high pressure resistance, heat resistance, explosion protection and corrosion resistance.

IP68 Waterproof Cable Connector Qualification

Certificates of PA66 Cable Gland: CE,ROHS, IP68,ISO9001





Deliver, Shipping And Serving

Delivery of PA66 Cable Gland : Normally 7 working days to 1 month after received the payment.

Tel: +86-18958708338 **E-mail:** jx5@jxljq.net