



## Metal Cable Gland



We have rich experience and strong strength and are recognized and loved by customers for JIXIANG CONNECTOR® Metal Cable Gland all over the world. We independently produce and design many types of #CablbeGlands and #CableConnectors, which can meet your various needs. Say Metal Cable Gland. More designs are welcome to communicate with us. We have strong R&D capabilities and can provide you with

OEM&ODM services for Metal Cable Gland.

### Product Description

You can rest assured to buy customized JIXIANG CONNECTOR® Metal Cable Gland from us. We look forward to cooperating with you, if you want to know more, you can consult us now, we will reply to you in time! The company has always been oriented by customer demand and respect for talents, constantly improve their strength, improve service level and quality. With many European and American, Asian and domestic customers, we have established long-term good relationship with common progress. Sincerely expect to join hands with you to create the future.

### China Metal Cable Gland ISO9001 Manufacturer

JIXIANG CONNECTOR® Metal Cable Gland may be used on all types of electrical power, control, instrumentation, data and telecommunications cables.

They are used as a sealing and termination device to ensure that the characteristics of the enclosure which the cable enters can be maintained adequately.

### Parameter (Specification) of Metal Cable Gland

Metal Cable Gland New Type – PG thread							
Product Code	Thread AG	Cable range(mm)	Thread O.D.(mm)	Mounting Hole Diameter (mm)	Thread length GL(mm)	Spanner Size (mm)	Std, Pkg (pcs)
JX-PG7A-MG	PG7	3-5.3	12.5	12.5-12.8	8	17/17	10
JX-PG7B-MG		4.5-7.8	12.5	12.5-12.8	8	17/17	10

JX-PG9A-MG	PG9	3-5.8	15.2	15.2-15.5	8	18/17	10
JX-PG9B-MG		4.5-7.8	15.2	15.2-15.5	8	18/17	10
JX-PG11A-MG	PG11	4-7	18.6	18.6-18.9	9	22/22	10
JX-PG11B-MG		6-10	18.6	18.6-18.9	9	22/22	10
JX-PG13.5A-MG	PG13.5	5-8.8	20.4	20.4-20.7	9.5	24/24	10
JX-PG13.5B-MG		7-12	20.4	20.4-20.7	9.5	24/24	10
JX-PG16A-MG	PG16	7-11	22.5	22.5-22.8	9.5	26/26	10
JX-PG16B-MG		9-14	22.5	22.5-22.8	9.5	26/26	10
JX-PG21A-MG	PG21	12-16	28.3	28.3-28.7	12	32/32	10
JX-PG21B-MG		14-18	28.3	28.3-28.7	12	32/32	10
JX-PG29A-MG	PG29	16-22	37	37-37.4	12.5	41/41	10
JX-PG29B-MG		18-25	37	37-37.4	12.5	41/41	10
JX-PG36A-MG	PG36	21-25	47	47-47.4	15	50/50	5
JX-PG36B-MG		24-30	47	47-47.4	15	50/50	5

### Feature And Application of Metal Cable Gland

Features: The claws and seals of excellent design, sealing nut have a “click” sound and re-open, can hold cable firmly and have a wider cable range. Resistant to salt water, weak acid, alcohol, oil, grease and common solvency.

Function: Metal Cable Gland is cable supporting products, connector cable can be locked, the other end of the device can access the device through the box body, also can choose thread access according to the entry and outlet of the internal thread electrical equipment.

More options: Customization is acceptable. Welcome to inquire when ordering.



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

### Details of Metal Cable Gland

Connection Thread: PG

Material:

Cap nut: Brass with nickel Plated

Clamping Insert: PA66

Sealing Ring: EPDM

Gland Body: Brass with nickel plated

Certificate: CE, IP68, ISO9001

Protection Class : IP68-10 BAR

Operating Temperature: -40 °C to +100 °C, (short time to 120 °C); -20 °C to 80 °C, (short time to 100 °C)

### Qualification of Metal Cable Gland

Certificates of Metal Cable Gland: CE,ROHS, REACH, IP68,ISO9001



### Deliver,Shipping And Serving

Delivery of Metal Cable Gland Normally 7 working days to 1 month after received the payment.