



Metric Cable Gland

Our JIXIANG CONNECTOR® Metric Cable Gland can be used in many fields, such as energy generation, rail transit, new energy vehicles, charging station systems, power electronic systems, heavy industry systems, etc. The Metric Cable Gland quality is reliable, safe and environmentally friendly. Basically, glands will be connected to panels, distribution boxes and electric equipments, etc. Simply message us with

your requirements and we will get back to you ASAP with a quote!

Product Description

As the professional manufacture, we would like to provide you high quality JIXIANG CONNECTOR® Metric Cable Gland. And we will offer you the best after-sale service and timely delivery. We firmly believe that perseverance is the key to the success of an enterprise. Continuous satisfaction of the needs of consumers is the basis for the survival of an enterprise, and products quality is the life of an enterprise. In recently years, the factory has won the sincere love of customers by relying on its sincere reputation, professional and enthusiastic service to convey the three excellent standard services of high quality materials, preferential prices and excellent service to our customers.

Metric Cable Gland Waterproof IP68 Factory from China

JIXIANG CONNECTOR® Metric Cable Gland may be used on all types of electrical power, control, instrumentation, data and telecommunications cables.

They are used as a sealing and termination device to ensure that the characteristics of the enclosure which the cable enters can be maintained adequately.

Parameter (Specification) of Metric Cable Gland

Metric Thread Series						
Product Code	Thread specification AG	Available cable range (mm)	Thread O.D. (mm)	Mounting Hole Diameter (mm)	Thread length GL (mm)	Spanner Size (mm)

JX-M12-TR	M12*1.5	6.5-3	12	12.12.2	7	14
JX-M14-TR	M14*1.5	6.5-3	14	14-14.2	7	17
JX-M16-TR	M16*1.5	8-4	16	16-16.2	7	18
JX-M18-TR	M18*1.5	10-5	18	18-18.2	8	20
JX-M20-TR	M20*1.5	12-6	20	20-20.2	8	22
JX-M22-TR	M22*1.5	14-10	22	22-22.2	8	24
JX-M27A-TR	M27*1.5	18-13	27	27-27.2	9	30
JX-M27B-TR	M27*2	18-13	27	27-27.2	9	30
JX-M28A-TR	M28*1.5	18-13	28	28-28.2	9	30
JX-M28B-TR	M28*2	18-13	28	28-28.2	9	30
JX-M30A-TR	M30*1.5	18-13	30	30-30.2	9	30/32
JX-M30B-TR	M30*2	18-13	30	30-30.2	9	30/32
JX-M32A-TR	M32*1.5	22-15	32	32-32.2	10	35
JX-M32B-TR	M32*2	22-15	32	32-32.2	10	35
JX-M33A-TR	M33*1.5	22-15	33	33-33.2	10	35
JX-M33B-TR	M33*2	22-15	33	33-33.2	10	35
JX-M37A-TR	M37*1.5	25-18	37	37-37.2	10	40
JX-M37B-TR	M37*2	25-18	37	37-37.2	10	40
JX-M40A-TR	M40*1.5	25-18	40	40-40.2	11	40/45
JX-M40B-TR	M40*2	25-18	40	40-40.2	11	40/45
JX-M47A-TR	M47*1.5	33-25	47	47-47.2	11	50
JX-M47B-TR	M47*2	33-25	47	47-47.2	11	50
JX-M48A-TR	M48*1.5	33-25	48	48-48.2	11	50/52
JX-M48B-TR	M48*2	38-32	48	48-48.2	11	50/52
JX-M54A-TR	M54*1.5	38-32	54	54-54.2	12	57
JX-M54B-TR	M54*2	38-32	54	54-54.2	12	57
JX-M56A-TR	M56*1.5	38-32	56	56-56.2	12	57/59
JX-M56B-TR	M56*2	38-32	56	56-56.2	12	57/59

JX-M60A-TR	M60*1.5	44-37	60	60-60.2	13	64
JX-M60B-TR	M60*2	44-37	60	60-60.2	13	64
JX-M63A-TR	M63*1.5	44-37	63	63-63.2	13	64/68
JX-M63B-TR	M63*2	44-37	63	63-63.2	13	64/68
JX-M64A-TR	M64*1.5	44-37	64	64-64.2	13	64/68
JX-M64B-TR	M64*2	44-37	64	64-64.2	13	64/68

Feature And Application of Metric Cable Gland

Features: The Metric Cable Gland is a product of large range, high tensile strength, waterproof, dustproof, salt, acid, alcohol, grease and common solvent resistant.

Function: Metric Cable Gland is cable supporting products, connector cable can be locked, the other end of the device can access the devices through the box body, also can choose thread access according to the entry and outlet of the internal thread electrical equipment.

More options: Customization of Metric Cable Gland is acceptable. Welcome to inquire when ordering.



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

Details of Metric Cable Gland

Products:

Thread Size: Metric Thread

Material: The joint body parts are made of nickel plated brass, the clamping part is made of plastic(PA), and the seals and O-ring seals are made of nitrile rubber (NBR).

Operating temperature: Static: -40 °C to 100 °C, short time up to 120 °C. Dynamic: -20 °C to 80 °C, short time up to 100 °C

Thread length: The short thin thread is suitable for holes in thin board or devices with internal thread, while the long thread is available for thick board. Long threads can be customized.

Qualification of Metric Cable Gland

Certificates of Metric Cable Gland: CE,ROHS, REACH, IP68,ISO9001



Deliver,Shipping And Serving

Delivery of Metric Cable Gland Normally 7 working days to 1 month after received the payment.