



### Nickel Plated Brass Cable Gland

We are Professional supplier in various kinds of Cable Glands and Cable Connectors. We supply JIXIANG CONNECTOR® Nickel Plated Brass Cable Gland with TUV, ROHS, REACH, CE, etc approved.

Customer First

Quality Ensured

Delivery on time

Customer satisfaction reaches 98.90%.

We are looking for partners and look forward to your cooperation !

### Product Description

Yueqing Jixiang Connector Co., Ltd. is JIXIANG CONNECTOR® Nickel Plated Brass Cable Gland manufacturers and suppliers in China who can wholesale Nickel Plated Brass Cable Gland. We can provide professional service and better price for you. And our focus is on maintaining a high level of professionalism, service, and quality. If you interested in Nickel Plated Brass Cable Gland products, please contact with us. We follow the quality of rest assured that the price of conscience, dedicated service.

### China Nickel Plated Brass Cable Gland Factory

JIXIANG CONNECTOR® Nickel Plated Brass Cable Gland may be used on all types of electrical power, control, instrumentation, data and telecommunications cables.

They are used as a sealing and termination device to ensure that the characteristics of the enclosure which the cable enters can be maintained adequately.

### Parameter (Specification) of Nickel Plated Brass Cable Gland

Nickel Plated Brass Cable Gland							
Product Code	Thread AG	Applicable cable range(mm)	Thread O.D.(mm)	Mounting Hole Diameter (mm)	Thread length GL(mm)	Joint length H(mm)	Spanner Size (mm)
JX-M6-NP	M6×1	3.5-1	6	6-6.2	5	11	8
JX-M8-NP	M8×1	5.5-2	8	8-8.2	5	16	12

JX-M10-NP	M10×1	6.5-3	10	10-10.2	7	19	14
JX-M12-NP	M12×1.5	6.5-3	12	12-12.2	7	19	14
JX-M14-NP	M14×1.5	8-4	14	14-14.2	7	19	17
JX-M16-NP	M16×1.5	8-4	16	16-16.2	8	20	18
JX-M18-NP	M18×1.5	10-5	18	18-18.2	8	21	20
JX-M20-NP	M20×1.5	12-6	20	20-20.2	8	22	22
JX-M22-NP	M22×1.5	14-10	22	22-22.2	8	23	24
JX-M24-NP	M24×1.5	14-10	24	24-24.2	9	25	24/27
JX-M25A-NP	M25×1.5	14-10	25	25-25.2	9	25	24/27
JX-M25B-NP	M25×1.5	16-8	25	25-25.2	9	27	27
JX-M25C-NP	M25×1.5	18-13	25	25-25.2	9	27	30/27
JX-M27A-NP	M27×1.5	18-13	27	27-27.2	9	27	30
JX-M27B-NP	M27×2	18-13	27	27-27.2	9	27	30
JX-M28A-NP	M28×1.5	18-13	28	28-28.2	9	27	30
JX-M28B-NP	M28×2	18-13	28	28-28.2	9	27	30
JX-M30A-NP	M30×1.5	18-13	30	30-30.2	9	29	30/32
JX-M30B-NP	M30×2	18-13	30	30-30.2	9	29	30/32
JX-M32A-NP	M32×1.5	22-15	32	32-32.2	10	29	35
JX-M32B-NP	M32×1.5	20-16	32	32-32.2	10	29	35
JX-M32C-NP	M32×2	22-15	32	32-32.2	10	29	35
JX-M33A-NP	M33×1.5	22-15	33	33-33.2	10	29	35
JX-M33B-NP	M33×2	22-15	33	33-33.2	10	29	35
JX-M36A-NP	M36×1.5	25-18	36	36-36.2	10	31	40
JX-M36B-NP	M36×2	25-18	36	36-36.2	10	31	40
JX-M37A-NP	M37×1.5	25-18	37	37-37.2	10	31	40
JX-M37B-NP	M37×2	25-18	37	37-37.2	10	31	40
JX-M40A-NP	M40×1.5	25-18	40	40-40.2	11	31	40/45
JX-M40B-NP	M40×2	25-18	40	40-40.2	11	31	40/45

JX-M40C-NP	M40×1.5	30-22	40	40-40.2	11	35	45
JX-M40D-NP	M40×2	30-22	40	40-40.2	11	35	45
JX-M42A-NP	M42×1.5	30-22	42	42-42.2	11	35	45
JX-M42B-NP	M42×2	30-22	42	42-42.2	11	35	45
JX-M47A-NP	M47×1.5	33-25	47	47-47.2	11	37	50
JX-M47B-NP	M47×2	33-25	47	47-47.2	11	37	50
JX-M48A-NP	M48×1.5	33-25	48	48-48.2	11	37	50/52
JX-M48B-NP	M48×2	33-25	48	48-48.2	11	37	50/52
JX-M50A-NP	M50×1.5	38-32	50	50-50.2	12	37	55/57
JX-M50B-NP	M50×2	38-32	50	50-50.2	12	37	55/57
JX-M54A-NP	M54×1.5	38-32	54	54-54.2	12	38	57
JX-M54B-NP	M54×2	38-32	54	54-54.2	12	38	57
JX-M56A-NP	M56×1.5	38-32	56	56-56.2	12	38	57/59
JX-M56B-NP	M56×2	38-32	56	56-56.2	12	38	57/59
JX-M60A-NP	M60×1.5	44-37	60	60-60.2	13	38	64
JX-M60B-NP	M60×2	44-37	60	60-60.2	13	38	64
JX-M63A-NP	M63×1.5	44-37	63	63-63.2	13	38	64/68
JX-M63B-NP	M63×2	44-37	63	63-63.2	13	38	64/68
JX-M64A-NP	M64×1.5	44-37	64	64-64.2	13	38	64/68
JX-M64B-NP	M64×2	44-37	64	64-64.2	13	38	64/68
JX-M72-NP	M72×2	52-42	72	72-72.2	15	42	78
JX-M75-NP	M75×2	52-42	75	75-75.2	15	42	78
JX-M80-NP	M80×2	62-50	80	80-80.2	15	45	86/88
JX-M88-NP	M88×2	70-60	88	88-88.2	15	45	98
JX-M100-NP	M100×2	84-78	100	100-100.2	15	45	110
JX-M110-NP	M110×2	90-80	110	110-110.2	20	57	120
JX-M120-NP	M120×2	102-90	120	120-120.2	20	57	135
JX-M125-NP	M125×2	108-98	125	125-125.2	24	65	135

JX-M150-NP	M150×2	125-110	150	150-150.5	25	70	160
------------	--------	---------	-----	-----------	----	----	-----

### Feature And Application of Nickel Plated Brass Cable Gland

Our JIXIANG CONNECTOR® Nickel Plated Brass Cable Gland can be used in many fields, such as energy generation, rail transit, new energy vehicles, charging station systems, power electronic systems, heavy industry systems, etc.

The Nickel Plated Brass Cable Gland quality is reliable, safe and environmentally friendly. Basically, Nickel Plated Brass Cable Gland will be connected to panels, distribution boxes and electric equipments, etc.



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

### Details of Nickel Plated Brass Cable Gland

Thread Specification: Metric Thread

Material: The Nickel Plated Brass Cable Gland body parts are made of brass, the clamping part is made of plastic(PA), and the seals and O-ring are made of nitrile rubber (NBR).

Certificates: CE,ROHS, REACH, IP68,ISO9001,TUV

Protection Degree: In the specific cable range, the using of O-ring helps tighten head so that to reach IP68-10 bar.

Operating temperature: Static: -40 °C to 100 °C, short time up to 120 °C. Dynamic: -20 °C to 80 °C, short time up to 100 °C

### Qualification of Nickel Plated Brass Cable Gland

Certificates of Nickel Plated Brass Cable Gland: CE,ROHS, REACH, IP68,ISO9001,TUV



### Deliver,Shipping And Serving

Delivery of Nickel Plated Brass Cable Gland: Normally 7 working days to 1 month after received the payment.