



PG Cable Gland

You can rest assured to buy JIXIANG CONNECTOR® PG Cable Gland from our factory and we will offer you the best after-sale service and timely delivery. We supply PG Cable Gland with TUV, ROHS, REACH, CE, etc approved.

Product Description

Yueqing Jixiang Connector Co., Ltd. is PG Cable Gland manufacturers and suppliers in China who can wholesale PG Cable Gland. We can provide professional service and better price for you. If you interested in PG Cable Gland products, please contact with us. We follow the quality of rest assured that the price of conscience, dedicated service. We have achieved remarkable success in this domain as a result of our focused approach, timely delivery, and ethical company philosophy.

China PG Cable Gland IP68 Price

JIXIANG CONNECTOR® PG Cable Gland may be used on all types of electrical power, control, instrumentation, data and telecommunications cables.

They are used as a sealing and termination device to ensure that the characteristics of the enclosure which the cable enters can be maintained adequately.

Parameter (Specification) of PG Cable Gland

Metal cable gland - PG thread series							
Product Code	Thread specification AG	Available cable range(mm)	Thread O.D (mm)	Mounting Hole Diamter (mm)	Thread Length GL(mm)	Joint Length H(mm)	Spanner size (mm)
JX-PG7-NP	PG7	6.5-3	12.5	12.5-12.7	7	19	14
JX-PG9-NP	PG9	8-4	15.2	15.2-15.4	8	20	18
JX-PG11-NP	PG11	10-5	18.6	18.6-18.8	8	21	20

JX-PG13.5-NP	PG13.5	12-6	20.4	20.4-20.6	8	22	22
JX-PG16-NP	PG16	14-10	22.5	22.5-22.7	9	23	24
JX-PG19A-NP	PG19	14-10	25	25-25.2	9	25	24/27
JX-PG19B-NP	PG19	16-8	25	25-25.2	9	25	27
JX-PG21A-NP	PG21	18-13	28.3	28.3-28.5	9	27	30/32
JX-PG21B-NP	PG21	16-9	28.3	28.3-28.5	9	27	30/32
JX-PG25-NP	PG25	22-15	32	32-32.2	10	29	35
JX-PG29-NP	PG29	25-18	37	37-37.2	11	31	40
JX-PG36-NP	PG36	33-25	47	47-47.2	12	37	50
JX-PG42-NP	PG42	38-32	54	54-54.2	13	38	57
JX-PG48-NP	PG48	44-37	59.3	59.3-59.5	14	38	64
JX-PG63NP	PG63	52-42	72	72-72.2	15	42	78

Feature And Application of PG Cable Gland

Features: The PG Cable Gland is a product of large scope, high tensile strength, waterproof, dustproof, salt, acid and alkali resistance, alcohol, oil and solvent resistance.

Function: PG Cable Gland is the product forms a complete set of the cable, connector cable can be locked, and the other end can access the devices through the box body, also can choose thread access according to the entry and outlet of the internal thread electric devices.

More options: Customization is acceptable. Welcome to inquire



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

Details of PG Cable Gland

Thread specification: PG

Product material: The PG Cable Gland body parts are made of brass, the clamping part is made of nylon (PA), and the seals and O-ring are made of nitrile rubber (NBR).

Certificates: CE, ROHS, IP68, ISO9001, TUV

Protection Degree: In the specific cable range, the using of O-ring helps tighten head so that to reach IP68-10 bar.

Working Temperature: : -40°C to 100 °C, short time of up to 120°C. Dynamic: - 20 °C to 80 °C, short time of up to 100 °C

Thread Length: The short thread suitable for holes in thin board or equipment with inner thread, while the long thread is available for thick plate. Threaded extension can be customized.

Qualification of PG Cable Gland

Certificates of PG Cable Gland CE,ROHS, REACH, IP68,ISO9001,TUV



Deliver,Shipping And Serving

Delivery of PG Cable Gland Normally 7 working days to 1 month after received the payment.