



Stainless Steel Screw Cap

We have our own factory for JIXIANG CONNECTOR® Stainless steel screw cap where we work closely with you from product development through bulk production and help you find saving you time and money while achieving the results you want. We serve our customers with professionalism and first-class standards, as well as a reasonable price system, and are well received by customers at home and abroad. We

look forward to cooperating with you.

Product Description

As a professional high quality JIXIANG CONNECTOR® Stainless Steel Screw Cap manufacture, you can rest assured to buy Stainless Steel Screw Cap from our factory and we will offer you the best after-sale service and timely delivery. "To achieve zero faults via continuous improvement, to satisfy our customers' needs and expectations, to make pledges we fully understand and think we can keep, and to keep all commitments to customers on schedule," is our guiding concept.

High Quality China Stainless Steel Screw Cap Factory Price

JIXIANG CONNECTOR® Stainless steel screw cap are used for secure sealing of unused threaded or clearance holes in housings etc.

Stainless Steel Screw Cap Parameter (Specification)

Circle Series Model	Hexagon Series Model	Thread specification AG	Thread length GL (mm)	H(mm)	D(mm)
JX-PG7-SSC	JX-PG7-SSH	PG7	5	8	14
JX-PG9-SSC	JX-PG9-SSH	PG9	6	9	17
JX-PG11-SSC	JX-PG11-SSH	PG11	6	9	20
JX-PG13.5-SSC	JX-PG13.5-SSH	PG13.5	6.5	9.5	22
JX-PG16-SSC	JX-PG16-SSH	PG16	6.5	9.5	24
JX-PG21-SSC	JX-PG21-SSH	PG21	7	11	30
JX-PG29-SSC	JX-PG29-SSH	PG29	8	12	39
JX-PG36-SSC	JX-PG36-SSH	PG36	9	15	50
JX-PG42-SSC	JX-PG42-SSH	PG42	10	16	57

JX-PG48- SSC	JX-PG48- SSH	PG48	10	16	64
JX-M12- SSC	JX-M12- SSH	M12	5	8	14
JX-M16- SSC	JX-M16- SSH	M16	6	9	17
JX-M18- SSC	JX-M18- SSH	M18	6	9	20
JX-M20- SSC	JX-M20- SSH	M20	6.5	9.5	22
JX-M22- SSC	JX-M22- SSH	M22	6.5	9.5	24
JX-M24- SSC	JX-M24- SSH	M24	6.5	10	27
JX-M25- SSC	JX-M25- SSH	M25	6.5	10	27
JX-M30- SSC	JX-M30- SSH	M30	6.5	10	33
JX-M32- SSC	JX-M32- SSH	M32	7	11	35
JX-M36- SSC	JX-M36- SSH	M36	8	12	39
JX-M40- SSC	JX-M40- SSH	M40	8	13	43
JX-M47- SSC	JX-M47- SSH	M47	9	15	50
JX-M50- SSC	JX-M50- SSH	M50	9	15	55
JX-M54- SSC	JX-M54- SSH	M54	10	16	57
JX-M60- SSC	JX-M60- SSH	M60	10	16	64
JX-M63- SSC	JX-M63- SSH	M63	10	16	66
JX-M72- SSC	JX-M72- SSH	M72	10	16	75

Stainless Steel Screw Cap Feature And Application

Features:

Stainless steel screw caps are in order to close the reserved holes or extra holes, make the product beautiful, it can keep waterproof, dust-proof, salt, acid, alcohol, oil and solvent resistant

Stainless steel screw cap allows for ease of cleaning, meaning that it is simple to maintain.

Stainless steel screw cap provides corrosion resistance, along with superior resistance to oxidation.

Application:

- Aerospace, ship and automotive structures
- Construction material for buildings
- Food processing equipment (such as wine, beer brewing, and milk)
- Kitchen equipment (such as sinks or appliances)



MECHANICAL EQUIPMENT



LIGHTING EQUIPMENT



NEW ENERGY VEHICLE



PHOTOVOLTAIC (PV)



OUTDOOR ADVERTISEMENTS



WHEEL TRANSPORT DOCK

Stainless Steel Screw Cap Details

Thread Size: Metric ,PG

Material: Stainless Steel 304/316

Sealing: Modified Rubber

Shape: Hexagonal, Round

Product Certification: CE

Protection Degree: IP68- 10 BAR

Working temperature: -40 °C to 100 °C in static state, or instantaneous heat resistance up to 120 °C; -20°C to 80°C in dynamic state, or instantaneous heat resistance up to 100°C.

More options: Customization of Stainless Steel screw cap is acceptable. Welcome to inquire.

Stainless Steel Screw Cap Qualification

Certificates of Stainless Steel screw cap: CE, IP68



Deliver,Shipping And Serving of Stainless Steel Screw Cap

Delivery of JIXIANG CONNECTOR® Stainless Steel screw cap: Normally 7 working days to 1 month after received the payment.

Product Recommend

[Nylon Screw Cap](#)

JIXIANG CONNECTOR® Nylon Screw caps are used for secure sealing of unused threaded or clearance holes in housings etc



Brass Screw Cap

JIXIANG CONNECTOR® Brass screw caps are used for secure sealing of unused threaded or clearance holes in housings etc.

Hex Head



Circle Head

