

## Hot Sell PG Clamps

Model:CAPG-B4



You can rest assured to buy Hot Sell PG Clamps from our factory and we will offer you the best after-sale service and timely delivery. The CAPG-B4 parallel groove clamps with two bolts are designed to connect aluminium conductors and copper conductors. These

connectors are composed of two parts, an upper body and lower body. Adopts advanced design idea and production technology that making casing, lead, U-shape screw,...

### Product Introduction

#### Hot Sell PG Clamps

The CAPG-B4 parallel groove clamps with two bolts are designed to connect aluminium conductors and copper conductors. These connectors are composed of two parts, an upper body and lower body. Adopts advanced design idea and production technology that making casing, lead, U-shape screw, pressure-article compact.

Special designed screw hole and arc shape of the body allow clamp to adjusts to different cable size on each side. Materials of bolt and nut are optional depend on customer request. Options including Hot-dip galvanized steel and Stainless steel.

The installation and use is simple, wire-clamps strength is high, without any magnetic hysteresis. Slotted holes allow adjustment for conductors on each side. Use a single spanner on galvanized nuts and bolts. Standard for aluminum-to-copper connections.

Besides this main area of application parallel groove clamps are also used for safety loops and therefore they must provide an adequate mechanical holding strength. An adequate mechanical holding strength is achieved. In case of higher values two or more PG-clamps should be used in series.

### TECHNICAL:

Model	CAPG-B4
Conductor Range (mm <sup>2</sup> )	Cu 50-240, Al 35-300
Bolt (Pcs)	2

**FAQ:**

Q1: Are you a trading company or factory?

A2: We are the factory.

Q2: What is the acceptable payment term?

A2: Credit Card, West Union, Paypal or T/T.

Q3: What is difference between CAPG and APG?

A3: CAPG is the bimetallic pg connector, and APG is aluminium pg connector.

Q4: What is the package could be?

A4: We can make special design as your requirement.

Q5: The PG Connector is for bare overhead networks?

A5: Used for tapping or joining AAC, AAAC or ACSR overhead conductors.

Q6: What is the difference for model A/B/C?

A6: A is for 1 bolt, B is for 2 bolts, C is for 3 bolts.

Q7: What is the guarantee?

A7: 1 Year under the normal service condition.