

Parallel Groove Connector Supplier

Model:CAPG-C1



Welcome to buy Parallel Groove Connector Supplier from us. Every request from customers is being replied within 24 hours. CAPG-C1 Parallel groove clamps are mainly used for transmitting current between the interconnected conductors, are designed to

connect two parallel conductors in order to do a derivation of a secondary conductor. In bimetallic PG clamps, the two bodies are made out of high strength aluminium...

Product Introduction

Parallel Groove Connector Supplier

CAPG-C1 Parallel groove clamps are mainly used for transmitting current between the interconnected conductors, are designed to connect two parallel conductors in order to do a derivation of a secondary conductor.

In bimetallic PG clamps, the two bodies are made out of high strength aluminium alloy.

If conductors made of different materials are to be connected this can be done by using bimetallic tubes. Adopts advanced design idea and production technology that making casing, lead, U-shape screw, pressure-article compact and have good contact in addition to big gripping-power after being assembled.

An adequate mechanical holding strength is achieved. In case of higher values two or more Parallel groove clamps should be used in series. Special designed screw hole and arc shape of the body allow clamp to adjust to different cable size on each side. Materials of bolt and nut are optional depend on customer request. Options including Hot-dip galvanized steel and Stainless steel. Pressure pad is applied to achieve uniform pressure along the clamp.

TECHNICAL:

Model	CAPG-C1
Conductor Range (mm ²)	Cu 6-50, Al 16-70
Bolt (Pcs)	3

FAQ:

Q1: Are you a trading company or factory?

A2: We are the factory.

Q2: What is the acceptable payment term?

A2: Credit Card, West Union, Paypal or T/T.

Q3: What is difference between CAPG and APG?

A3: CAPG is the bimetallic pg connector, and APG is aluminium pg connector.

Q4: What is the package could be?

A4: We can make special design as your requirement.

Q5: The PG Connector is for bare overhead networks?

A5: Used for tapping or joining AAC, AAAC or ACSR overhead conductors.

Q6: What is the difference for model A/B/C?

A6: A is for 1 bolt, B is for 2 bolts, C is for 3 bolts.

Q7: What is the guarantee?

A7: 1 Year under the normal service condition.