



Soap Coated Stainless Steel Wire

Ningbo Dingyan Metal Products Co.,Ltd. is a professional manufacturer and supplier of soap coated stainless steel wire from China,we have been specialized in spring wire for years.With high quality and competitive price,we have won good feedback from our customers all over the world. We welcome all the customers and partners to visit our factory for the win-win business cooperation.

Product Description

The soap coated stainless steel wire is made of high quality alloy wire with high-temperature-proof and corrosion-resisitant mateirals of stainless steel, according to international standard ASTM A313/JIS G4314/EN 10270-3. The soap coated stainless steel wire is widely used for spring producing, including compression spring, tension spring, torsion spring for automobile, medical and electrical industries and pump



sprayers.



Product Parameter (Specification)

1 Toddot I didiliotor (opooliiodilori)								
Norminal Diameter(mm)	Standard	Tolerance(mm)	Surface Finish	Tensile Strength (N/mm ₂)				
0.25-0.40	ASTM A313/ JIS G4314/ EN	±0.005		2050-2300				
0.40-0.60		±0.005	Soap-Coated/	1950-2200				
0.60-1.00		±0.008	Bright	1850-2100				
1.00-1.40	10270-3	±0.010		1750-2000				



www.dyspringwire.com

1.40-2.00	±0.010	1650-1900
2.00-2.50	±0.020	1550-1800
2.50-4.00	±0.020	1450-1700

Product Details

The soap coated stainless steel wire can be available for choice with size range of 0.25mm to 4.00mm in bright finish.



Bright





Soap-coated

Chemical composition:

	Grades		Chemical Composition							
AST M	JIS	EN	С	Si	Р	S	Ν	Mn	Cr	Ni
304	SUS304	1.430 1	≤0.08	≤1.0 0	≤0.04 5	≤0.0 3	-	≤2.0 0	18.00-20. 00	8.00-10.5 0



www.dyspringwire.com

304L	SUS304 L	1.430 6	≤0.03	≤1.0 0	≤0.04 5	≤0.0 3		≤2.0 0	18.00-20. 00	8.00-11.0
304H	SUS304 H	1.494 8	0.04-0. 10	≤1.0 0	≤0.04 5	≤0.0 3		≤2.0 0	18.00-20. 00	8.00-11.0
316	SUS316	1.440 1	≤0.08	≤1.0 0	≤0.03 5	≤0.0 3	-	≤2.0 0	16.00-18. 00	10.00-14. 00

Packing:

We can arrange packing with coils, spools, pallets and wooden cases.





Coils



Plastic spools

Norminal Diameter(mm)	Packing	Approx. Weight		
0.25-0.35	DIN200 Spool/Coil	10-20kg		
0.35-0.60	DIN250 Spool/Coil	15-30kg		
0.60-1.50	Coil	50kg		
1.50-2.00	Coil	50kg		
2.00-4.00	Coil	100kg		

Advantages:

- -Elemental composition is more stable;
- -Better in corrosion resistance and high temperature proof, suitable for strong corrosive and high temperature environment;
- -Steel ring quality:the surface of the product is smooth without cracks,safe to use;
- -The products strictly use standard raw materials, and strictly control the product quality during the production process.



