



2	Pin	Copper Alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		300/8	/	300/8
EC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		II/2		
额定电压/电流/Rated Voltage(V)/Current(A)		250/7		
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		2.5		
间距/Pitch(mm)/绝缘范围/Poles		3.50/N=02~24P		
使用温度范围/Operating Temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

公差表差 (General tolerances)(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±0.93	±1.05
±1.15	±1.60
±2.20	±2.50
±2.50	

MATERIAL:	SURFACE:
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
SIZE: A4	mm (inch)
NAME:	DRAWING NO.:
15ESARC-3.5-XXP-1Y-00A(H)	
TYPE:	SCALE:
REV	SHEET
1/1	1/1



宁波三安电子科技有限公司  
Sanan Electrical Technology Co., Ltd