



ULCUL 拔头参数		SALIS			
ULCUL Technical Data					
等级	Use Group	B	C	D	
额定电压	Rated Voltage	IV	300	-	300
额定电流	Rated Current	IA	10	-	10
导线范围	Wire Range	2#-12			
单/多芯线	Strd/Stranded	AWG	-		
耐电压	Withstanding Voltage	1000V/1min			
EC 拔头参数					
EC Technical Data					
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage	IV	-	320	630
额定电流	Rated Current	IA	-	15	15
额定冲击电压	Impulse withstand voltage	[KV]	-	4.0	4.0
导线横截面积	Conductor cross section	25			
镀层/漆层/导线	Strd/Insulate	[mm ²]			
材料	Material				
绝缘材料	Insulation Material	PA66			
阻燃等级	Inflammability	UL94V-0			
导体材料	Conductor Material	铜合金 Copper alloy			
导体表面镀层	Conductive Coating	镀锡 Hot plating			
一般参数 Other Data					
间距	Pitch	[mm]	5.0		
数量	Pieces	[PJ]	2#4		
导线长度	Stripping Length	[mm]	10-11		
扭矩	Screw/Torque Torque(Nm)	[Nm]	-		
工作温度	Operating temperature	[°C]	-40~+105		
引脚尺寸	Pin Dimensions	[mm]	-		
PCBA孔径	PCB Hole Diameter	[mm]	-		

公差 (General)	公差 (mm)
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±0.80	±1.05
±1.05	±1.15
±1.60	±2.20
±2.50	

0.1/10	±Z
--------	----

MATERIAL:	SURFACE:	
MAT NO.:	DRAWING NO.: ZESAKN-5.08	
STATUS:	NAME: 宁波三安电子科技有限公司 Sanan Electrical Technology Co., Ltd	
APPD:	SCALE: 1/1	
CHKD:	SHEET 1/1	
DRT:	REV	
SIZE: A4	TYPE: SHEET	