



2	Pin	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准	UL Standard:	B	C
额定电压/电流	/Rated Voltage(V)/Current(A)	300/8	300/8
额定冲击电压	(KV)/Rate Impulse Voltage(KV)	/	/
EC 标准	/IEC Standard:		
过压类别	/Overvoltage Category/污染等级/ Pollution Degree	II/2	
额定电压/电流	/Rated Voltage(V)/Current(A)	250/7	
额定冲击电压	(KV)/Rate Impulse Voltage(KV)	2.5	
间距/Pitch	(mm)/线数范围/Poles	3.81/N=02~24P	
使用温度范围	/Operating temperature(°C)	-40~+105	
符合RoHS环保要求	/Conform to RoHS	Yes	

SURFACE:



NAME: 15ESARC-3.81-XXP-1Y-00A(H)

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
DRAWING NO.:	
TYPE:	
SCALE:	
SHEET	REV
1/1	1/1

公差 (General tolerances)(mm)	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	~	~	~	~	~	~	~	~	~	~	~	~	~
	3	6	10	18	30	50	80	120	180	250	315	400	500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.50

公差	0.1/10
公差	±Z