



3	Screw cap	Copper alloy	/
2	Pin	Copper alloy	/
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电压/Rated Voltage(V)/Current(A)		300/8	300/8
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category /污染等级/ Pollution Degree		III/3	II/2
额定电压/电压/Rated Voltage(V)/Current(A)		/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		/	250/7
使用温度范围/Operating temperature(°C)		3.81/N=02~24P	-40~+105
符合RoHS环保要求/Conform to RoHS		Yes	

SURFACE:

**宁波三安电子科技有限公司**  
Sanan Electrical Technology Co. Ltd

NAME: 15ESARM-3.81-XXP-1Y-00A(H)

MATERIAL:  
MAT NO.:  
STATUS:  
APPD:  
CHKD:  
DRT:

DRAWING NO.:  
SCALE:  
SHEET

公差/General tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50	

表面粗糙度/General tolerances(mm)	0.1/10
表面粗糙度/General tolerances(mm)	±Z

尺寸/Size	A4
比例/Scale	1/1