



公差/General tolerances(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±1.05	±1.05
±1.15	±1.60
±2.20	±2.50

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRFT:	
SIZE: A4	
TYPE:	
SCALE:	
SHEET	1/1

NAME:	8ESAKRB-5.0-XXP-11-01A(H)	
DRAWING NO.:		
NAME:	宁波三安电子科技有限公司 Sanan Electrical Technology Co. Ltd	
SURFACE:	PANTONE 7534u	
UL 标准/UL Standard:	B	C D
额定电压/电源/Rated Voltage(V)/Current(A)	300/15	300/10
EC 标准/IEC Standard:		
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/3	II/2 I/1/2
额定电压/电源/Rated Voltage(V)/Current(A)		320/20
额定脉冲电压 (KV)/Rate Impulse Voltage(KV)		4
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm² /AWG)		0.2~2.5/22~14
间距/Pitch(mm)/线数范围/Poles		5.00/N=02~24P
剥线长度/Stripping length(mm)		9-10
使用温度范围/Operating temperature(°C)		-40~+105
符合RoHS环保要求/Conform to RoHS		Yes
标准颜色编号/Standard color number:	PANTONE 7534u	

ITEM	NAME OF PART	MATERIAL	NOTES
1	Cover	PA66	UL94V-0
2	Housing1	PA66	UL94V-0
3	Housing2	PA66	UL94V-0
4	Pin	Copper	Sn plated
5	Spring	Stainless steel	/
6	housing3	PA66	UL94V-0