



| ITEM | NAME OF PART | MATERIAL | NOTES |
|------|----------------|--------------|-----------|
| 7 | Hook 2 | PA66 | UL94V-0 |
| 6 | Hook 1 | PA66 | UL94V-0 |
| 5 | Spring | Copper alloy | Sn Plated |
| 4 | Clamp | Copper alloy | Sn Plated |
| 3 | Side Housing2 | PA66 | UL94V-0 |
| 2 | Housing | PA66 | UL94V-0 |
| 1 | Side Housing 1 | PA66 | UL94V-0 |

| UL 标准/UL Standard | B | C | D |
|---|------------|---------------|--------|
| 额定电压/Rated Voltage(V)/Current(A) | 300/10 | / | 300/10 |
| IEC 标准/IEC Standard | | | |
| 过压类别/Overvoltage Category/污染等级/Pollution Degree | III/3 | II/2 | II/2 |
| 额定电压/Rated Voltage(V)/Current(A) | 250/10 | / | / |
| 额定电压/电涌/浪涌电压(V)/Current(A) | 250/10 | 25-14.0/2-1.5 | / |
| 额定电压/电涌/浪涌电压(V)/Current(A) | 250/10 | 25-14.0/2-1.5 | / |
| 额定电压/电涌/浪涌电压(V)/Current(A) | 250/10 | 25-14.0/2-1.5 | / |
| 使用温度范围/Operating Temperature(°C) | 35N-02-24P | | |
| 符合RoHS环保要求/Conform to RoHS | Yes | | |

| 公差/General tolerances(mm) | |
|---------------------------|-------|
| 0 | >3 |
| ~ | >6 |
| ~ | >10 |
| ~ | >18 |
| ~ | >30 |
| ~ | >50 |
| ~ | >80 |
| ~ | >120 |
| ~ | >180 |
| ~ | >250 |
| ~ | >315 |
| ~ | >400 |
| ~ | >500 |
| ±0.12 | ±0.18 |
| ±0.22 | ±0.26 |
| ±0.31 | ±0.37 |
| ±0.57 | ±0.63 |
| ±1.05 | ±1.15 |
| ±1.60 | ±2.20 |
| ±2.50 | |

| 表面粗糙度/Surface Roughness |
|-------------------------|
| 0.1/10 |
| ±Z |

| | |
|-----------|---|
| MATERIAL: | SURFACE: |
| MAT NO.: | |
| STATUS: | |
| APPD: | |
| CHKD: | NAME: 宁波三安电子科技有限公司 Sanan Electrical Technology Co. Ltd |
| DRAFT: | DRAWING NO.: BESAKG-3.5-XXP-11-01A&Z(H) |
| SIZE: A4 | TYPE: |
| SCALE: | SCALE: 1/1 |

1 2 3 4 5 6

A B C D