



ABC Suspension Clamp Dead End Clamp Transmission Line Fitting Overhead Power Line Fitting

Model:DR1400

Jecsany as one of the professional China ABC Suspension Clamp Dead End Clamp Transmission Line Fitting Overhead Power Line Fitting manufacturers and factory, we are strong

strength and complete management. Also, we have own exporting license. We mainly deal in making a series of ABC Suspension Clamp Dead End Clamp Transmission Line Fitting Overhead Power Line Fitting and so on. We stick to the principal of quality orientation and customer priority, we sincerely welcome your letters, calls and investigations for business cooperation. We assure you of our high quality services at all time.

Product Introduction

Hot sale quality ABC Suspension Clamp Dead End Clamp Transmission Line Fitting Overhead Power Line Fitting with Low Price made in China. Jecsany is a ABC Suspension Clamp Dead End Clamp Transmission Line Fitting Overhead Power Line Fitting manufacturer and supplier in China. This anchoring assembly is used for the single anchoring of A.B.C.(Aerial Bundled Conductors) with insulated neutral messenger. It comprises a bracket supporting one or two anchoring clamps.

Product Parameter (Specification)

Code	DR1400	DR1500	DR1600	JBG-1
Cable Size	50-70mm ²	50-70mm ²	50-70mm ²	50-70mm ²
Breaking Load	20.8KN	20.8KN	20.8KN	20.8KN

Product Feature And Application

Feature	Dead End clamps are characterized by high mechanical stability ,reduced dimensions for easier handling ,high mechanical and climatic resistance . Cable gripping device in insulating material ensures the double insulation of the neutral core and avoids damage to sheath ,secured parts ,no tools required. Stainless steel tail with two blocks compressed on the end ,this connction allows an easier locking on the body of the clamp .They are in accordance with NFC 33-041.
Material	High strength aluminium alloy, nylon plus fiber glass, stainless steel
Use	This anchoring assembly is used for the single anchoring of A.B.C.(Aerial Bundled

	Conductors) with insulated neutral messenger. It comprises a bracket supporting one or two anchoring clamps.
Installation	Open the screw and put conductors into grooves. Tighten the shear head nut.
Standard	NFC 33-042; EN 50-483

Product Details



