

Adjustable Plastic Cable Clamp Wire Clips For Insulated Neutral Messenger



Model:STA

Jecsany as the professional manufacturer, we would like to provide you Adjustable Plastic Cable Clamp Wire Clips For Insulated Neutral Messenger. Dead End clamps are characterized by high

mechanical stability ,reduced dimensions for easier handling ,high mechanical and climatic resistance . Cable gripping device in insulating material ensures the double insulation of the neutral core and avoids damage to sheath ,secured parts ,no tools required. Stainless steel tail with two blocks compressed on the end ,this connection allows an easier locking on the body of the clamp .They are in accordance with NFC 33-041.

Product Introduction

Wholesale low price Adjustable Plastic Cable Clamp Wire Clips For Insulated Neutral Messenger made in China. Jecsany is a Adjustable Plastic Cable Clamp Wire Clips For Insulated Neutral Messenger manufacturer and supplier in China. This anchoring assembly is used for the single anchoring of A.B.C.(Aerial Bundled Conductors) with insulated neutral messenger. It comprises a bracket supporting one or two anchoring clamps.

Product Parameter (Specification)

Model	Cross-section (mm ²)
STA	1×10/1×16
STB	2×16/2×25
STC	4×16/4×25
STD	1×16/1×70
LA1	4×16/4×25
LA2	2×6/2×16
DCR-1	1×4/1×25
DCR-2	1×4/1×25
2.1	16-25
PA1500	25-50
PA2000	54.6-70

Product Feature And Application

Feature	Dead End clamps are characterized by high mechanical stability ,reduced dimensions for easier handling ,high mechanical and climatic resistance . Cable gripping device in insulating material ensures the double insulation of the neutral core and avoids damage to sheath ,secured parts ,no tools required. Stainless steel tail with two blocks compressed on the end ,this connction allows an easier locking on the body of the clamp .They are in accordance with NFC 33-041.
Material	High strength aluminium alloy, nylon plus fiber glass, stainless steel
Use	This anchoring assembly is used for the single anchoring of A.B.C.(Aerial Bundled Conductors) with insulated neutral messenger. It comprises a bracket supporting one or two anchoring clamps.
Installation	Open the screw and put conductors into grooves.Tighten the shear head nut.
Standard	NFC 33-042; EN 50-483

Product Details

