



APG-A1 Adjustable Bolt Type Aluminum Parallel Groove PG Clamp

Model:APG-A1

Jecsany is a professional leader China APG-A1 Adjustable Bolt Type Aluminum Parallel Groove PG Clamp manufacturer with high quality and reasonable price.Parallel Groove CLAMP is used for connecting or branching AAC,AAAC or ACSR overhead conductors. Forging creates a high strength clamp.Slotted holes allow adjustment for varying conductors on each side.Its type test is in accordance with IEC6238-1.

Product Introduction

Low Price Quality APG-A1 Adjustable Bolt Type Aluminum Parallel Groove PG Clamp In Stock. Jecsany is a APG-A1 Adjustable Bolt Type Aluminum Parallel Groove PG Clamp manufacturer and supplier in China. APG-A1 Parallel Groove Connector is used for the Non-bearing connection and offset of aluminum stranded wire, aluminum stranded wire, it's used with insulating cover for the effect of protective and insulation.

Product Parameter (Specification)

Type	Conductor Range	No. x Bolts
APG-A1	Al 16-70 mm ²	1 x M8
APG-A2	AL16-150 mm ²	1 x M8
APG-B2	Al 16-70 mm ²	2 x M8
APG-B3	AL 16-150 mm ²	2 x M8
APG-B4	AL 25-240 mm ²	2 x M10
APG-C1	AL 16-70 mm ²	3 x M8
APG-C2	AL 16-150 mm ²	3 x M8
APG-C3	AL 25-240 mm ²	3 x M10
APG-C4	AL 35-300 mm ²	3 x M10

Product Feature And Application

Material:	Aluminium
Structure:	C Clamp

Measurement system:	Metric
Usage:	Heavy Duty

Packaging & Delivery

Selling Units: Single item

Single package size: 35.5X18.5X24.5 cm

Single gross weight: 0.082 kg

Package Type: Box, Carton, Pallet or Crate

Lead Time:

Quantity(Piece)	1 - 100	101 - 1000	>1000
Est. Time(days)	15	25	To be negotiated

Feature

Pressure pad ensures pressure along the clamp evenly, Parallel groove clamp has high mechanical pullout strength and good electrical contact.

Material

Connector bodies made of corrosion resistant, high strength aluminum alloy 99.5;

Bolts: DIN 933, Grade 8.8, dacromet plated; Nut: DIN934, dacromet plated, pressed into lower part of PG clamp;

Pressure pad: aluminum alloy; Spring washer: DIN127, steel.

Spring washers: Steel, DIN6796 corrosion-protected, dacromet plated;

Stainless steel bolts and nuts are available according to the firm order.

Type and Size

General type and size or according to customer's drawing or sample.

Application

Suitable to connect two parallel bare conductors. Conductors can be aluminum alloy or aluminum steel reinforced and copper conductor.

Product Details



APG-A1