



### APG-B3 Corrosion Resistant Double Bolts Parallel Groove Electrical Wire PG Clamp

Model:APG-B3

You are welcomed to come to Jecsany factory to buy the latest selling, low price, and high-quality APG-B3 Corrosion Resistant Double Bolts Parallel Groove Electrical Wire PG Clamp.Parallel Groove CLAMP is used for connecting or branching AAC,AAAC or ACSR overhead conductors. Forging creates a high strength clamp.Slotted holes allow adjustment

for varying conductors on each side.Its type test is in accordance with IEC6238-1.

#### Product Introduction

Hot Sale China v Manufacturers and Suppliers. Jecsany is a APG-B3 Corrosion Resistant Double Bolts Parallel Groove Electrical Wire PG Clamp manufacturer and supplier in China. APG Parallel Groove Connector is used for the Non-bearing connection and offset of aluminum stranded wire, aluminum stranded wire, it's used with insulating cover for the effect of protective and insulation.

#### Product Parameter (Specification)

Type	Conductor Range	No. x Bolts
APG-A1	Al 16-70 mm <sup>2</sup>	1 x M8
APG-A2	AL 16-150 mm <sup>2</sup>	1 x M8
APG-B2	Al 16-70 mm <sup>2</sup>	2 x M8
APG-B3	AL 16-150 mm <sup>2</sup>	2 x M8
APG-B4	AL 25-240 mm <sup>2</sup>	2 x M10
APG-C1	AL 16-70 mm <sup>2</sup>	3 x M8
APG-C2	AL 16-150 mm <sup>2</sup>	3 x M8
APG-C3	AL 25-240 mm <sup>2</sup>	3 x M10
APG-C4	AL 35-300 mm <sup>2</sup>	3 x M10

#### Product Feature And Application

Material:	Aluminium
Structure:	C Clamp
Measurement system:	Metric
Usage:	Pipe Clamp

**Packaging & Delivery**

Selling Units: Single item

Single package size: 38X22.5X18.5 cm

Single gross weight: 0.144 kg

Package Type: Box, Carton, Pallet or Crate

**Lead Time:**

Quantity(Piece)	1 - 100	101 - 1000	>1000
Est. Time(days)	15	25	To be negotiated

**Feature**

Pressure pad ensures pressure along the clamp evenly, Parallel groove clamp has high mechanical pullout strength and good electrical contact.

**Material**

Connector bodies made of corrosion resistant, high strength aluminum alloy 99.5;

Bolts: DIN 933, Grade 8.8, dacromet plated; Nut: DIN934, dacromet plated, pressed into lower part of PG clamp;

Pressure pad: aluminum alloy; Spring washer: DIN127, steel.

Spring washers: Steel, DIN6796 corrosion-protected, dacromet plated;

Stainless steel bolts and nuts are available according to the firm order.

**Type and Size**

General type and size or according to customer's drawing or sample.

**Application**

Suitable to connect two parallel bare conductors. Conductors can be aluminum alloy or aluminum steel reinforced and copper conductor.

**Product Details**

