



DTL-2 Type 240 mm² Aluminum Copper Electrical Cable Lugs Types Terminals

Model:DTL-2-240-13

Find a huge selection of DTL-2 Type 240 mm² Aluminum Copper Electrical Cable Lugs Types Terminals from China at Jecsany. DTL-2 series of copper-aluminum wiring terminal is suitable for transition of the circular aluminum wires, hemicycle-sector aluminum wire, power supply cable in the distribution equipment and copper terminals of the electrical equipment. The products adopt friction

welding workmanship, It has advantage of good electric conductance, electrochemical corrosion resistance, long service life.

Product Introduction

Factory Direct Sale Quality DTL-2 Type 240 mm² Aluminum Copper Electrical Cable Lugs Types Terminals with Low Price Manufacturers and Suppliers. DTL-2-240-13 bi-metal cable lug used for termination and wiring connecting. Made from the highest quality aluminium and copper, joined using a friction welding process, the barrels are filled with a jointing compound, breaks the oxide layers on the aluminium.

All bi-metal cable lug follow IEC 61238-1 standard. We are able to produce special bimetal lugs on request.

Product Parameter (Specification)

Type A(mm)	P±0.3	D±0.5	d±0.3	L±3	L1±0.3	W±0.5	S±0.3
DTL-2-16-11	Φ11	Φ16	Φ6	80	40	Φ20	3
DTL-2-25-11	Φ11	Φ16	Φ7	80	40	Φ20	3
DTL-2-35-11	Φ11	Φ16	Φ8.5	80	40	Φ20	3
DTL-2-50-13	Φ13	Φ20	Φ10	90	43	Φ25	4.5
DTL-2-70-13	Φ13	Φ20	Φ11.5	90	43	Φ25	4.5
DTL-2-95-13	Φ13	Φ20	Φ13.5	90	43	Φ25	4.5
DTL-2-120-13	Φ13	Φ25	Φ15	115	59	Φ30	5.5
DTL-2-150-13	Φ13	Φ25	Φ16.5	115	59	Φ30	5.5

DTL-2-185-13	Φ13	Φ32	Φ18.5	122	60	Φ35	6
DTL-2-240-13	Φ13	Φ32	Φ21	122	60	Φ35	6
DTL-2-300-13	Φ13	Φ34	Φ23.5	128	65	Φ35	6
DTL-2-400-17	Φ17	Φ40	Φ26	160	90	Φ36	6
DTL-2-500-17	Round Head Φ17	Φ40	Φ30	160	95	Φ36	6
DTL-2-500	Squre Head	Φ47	Φ30	205	95	60*60	10
DTL-2-630-17	Round Head	Φ47	Φ33.5	205	95	60	10
DTL-2-630	Squre Head	Φ47	Φ33.5	205	95	60*60	10
DTL-2-800	Round Head	Φ60	Φ38.5	240	110	80	10
DTL-2-800	Squre Head	Φ60	Φ38.5	240	110	80*80	10
DTL-2-1000	Round Head	Φ60	Φ43.5	240	110	80	10
DTL-2-1000	Squre Head	Φ60	Φ43.5	240	110	80*80	10

Product Feature And Application

Material:	Aluminum L3 and copper T2
Working temperature:	-55℃ to +150℃
Application:	Terminal connectors are used to connect tap conductor to power equipments (transformer, circuit breaker, disconnect switch etc) or to wall bushing of substation.

Selling Units: Single item

Single package size: 9X2.5X2.5 cm

Single gross weight: 0.19 kg

Package Type: Box, Carton, Pallet or Crate

Lead Time:

Quantity(Piece)	1 - 10	11 - 500	501 - 1000	>1000
Est. Time(days)	15	20	30	To be negotiated

Product Details



