

## DTL-2 Type 70 Mm<sup>2</sup> Round Copper Lugs Types Terminal for Power Cable



Model:DTL-2-70-13

Jecsany as the professional manufacturer, we would like to provide you DTL-2 Type 70 Mm<sup>2</sup> Round Copper Lugs Types Terminal for Power Cable. Cable terminal lug is a kind of accessory for electrical connections, which can be crimped on cable/wire/ electrical equipment without thermal treatment. Our company supplies a wide range of premium quality lugs to satisfy different demands. Our products are designed,

manufactured and tested as per CE and GB standards to ensure good performance.

### Product Introduction

Buy DTL-2 Type 70 Mm<sup>2</sup> Round Copper Lugs Types Terminal for Power Cable made in China. Jecsany is a DTL-2 Type 70 Mm<sup>2</sup> Round Copper Lugs Types Terminal for Power Cable manufacturer and supplier in China. The DTL-2-70-13 Cu-Al Bimetal Cable Lugs are suitable for transition connection of the circular aluminium wires, hemisphere-sector aluminium wires, power supply cables in the distribution equipment and copper terminals of the electrical equipment. They are made from Cu 99.9% purity and Al 99.5 purity. The technology of friction welded is wonderfully adopted. Therefore they have distinguishing features of strong weld intensity, good nature in electrification, resistant galvanic corrosion and long service life.

### Product Parameter (Specification)

Type A(mm)	P±0.3	D±0.5	d±0.3	L±3	L1±0.3	W±0.5	S±0.3
DTL-2-16-11	Φ11	Φ16	Φ6	80	40	Φ20	3
DTL-2-25-11	Φ11	Φ16	Φ7	80	40	Φ20	3
DTL-2-35-11	Φ11	Φ16	Φ8.5	80	40	Φ20	3
DTL-2-50-13	Φ13	Φ20	Φ10	90	43	Φ25	4.5
DTL-2-70-13	Φ13	Φ20	Φ11.5	90	43	Φ25	4.5
DTL-2-95-13	Φ13	Φ20	Φ13.5	90	43	Φ25	4.5
DTL-2-120-13	Φ13	Φ25	Φ15	115	59	Φ30	5.5
DTL-2-150-13	Φ13	Φ25	Φ16.5	115	59	Φ30	5.5
DTL-2-185-13	Φ13	Φ32	Φ18.5	122	60	Φ35	6
DTL-2-240-13	Φ13	Φ32	Φ21	122	60	Φ35	6
DTL-2-300-13	Φ13	Φ34	Φ23.5	128	65	Φ35	6

DTL-2-400-17	Φ17	Φ40	Φ26	160	90	Φ36	6
DTL-2-500-17	Round Head Φ17	Φ40	Φ30	160	95	Φ36	6
DTL-2-500	Squre Head	Φ47	Φ30	205	95	60*60	10
DTL-2-630-17	Round Head	Φ47	Φ33.5	205	95	60	10
DTL-2-630	Squre Head	Φ47	Φ33.5	205	95	60*60	10
DTL-2-800	Round Head	Φ60	Φ38.5	240	110	80	10
DTL-2-800	Squre Head	Φ60	Φ38.5	240	110	80*80	10
DTL-2-1000	Round Head	Φ60	Φ43.5	240	110	80	10
DTL-2-1000	Squre Head	Φ60	Φ43.5	240	110	80*80	10

### Product Feature And Application

Material:	Aluminum L3 and copper T2
Working temperature:	-55℃ to +150℃
Application:	Terminal connectors are used to connect tap conductor to power equipments (transformer, circuit breaker, disconnect switch etc) or to wall bushing of substation.

Selling Units: Single item

Single package size: 9X2.5X2.5 cm

Single gross weight: 0.19 kg

Package Type: Box, Carton, Pallet or Crate

### Lead Time:

Quantity(Piece)	1 - 10	11 - 500	501 - 1000	>1000
Est. Time(days)	15	20	30	To be negotiated

### Product Details





