

## DTL-2 Type Copper Aluminum Wiring Connecting Tube Crimp Type

Model:DTL-2-50-13



You can rest assured to buy DTL-2 Type Copper Aluminum Wiring Connecting Tube Crimp Type from Jecsany factory and we will offer you the best after-sale service and timely delivery. DTL-2 series of copper-aluminum wiring terminal is suitable for transition of the circular aluminum wires, hemicycle-sector aluminum wire, power supply cable in the distribution equipment

and copper terminals of the electrical equipment. The products adopt friction welding workmanship, It has advantage of good electric conductance, electrochemical corrosion resistance, long service life.

### Product Introduction

Professional China quality DTL-2 Type Copper Aluminum Wiring Connecting Tube Crimp Type Manufacturers and Suppliers. Jecsany is a DTL-2 Type Copper Aluminum Wiring Connecting Tube Crimp Type manufacturer and supplier in China. DTL-2-50-13 bi-metal cable lug used for termination and wiring connecting. Made from the highest quality aluminium and copper, joined using a friction welding process, the barrels are filled with a jointing compound, breaks the oxide layers on the aluminium.

All bi-metal cable lug follow IEC 61238-1 standard. We are able to produce special bimetal lugs on request.

### Product Parameter (Specification)

| Type A(mm)   | P±0.3 | D±0.5 | d±0.3 | L±3 | L1±0.3 | W±0.5 | S±0.3 |
|--------------|-------|-------|-------|-----|--------|-------|-------|
| DTL-2-16-11  | Φ11   | Φ16   | Φ6    | 80  | 40     | Φ20   | 3     |
| DTL-2-25-11  | Φ11   | Φ16   | Φ7    | 80  | 40     | Φ20   | 3     |
| DTL-2-35-11  | Φ11   | Φ16   | Φ8.5  | 80  | 40     | Φ20   | 3     |
| DTL-2-50-13  | Φ13   | Φ20   | Φ10   | 90  | 43     | Φ25   | 4.5   |
| DTL-2-70-13  | Φ13   | Φ20   | Φ11.5 | 90  | 43     | Φ25   | 4.5   |
| DTL-2-95-13  | Φ13   | Φ20   | Φ13.5 | 90  | 43     | Φ25   | 4.5   |
| DTL-2-120-13 | Φ13   | Φ25   | Φ15   | 115 | 59     | Φ30   | 5.5   |
| DTL-2-150-13 | Φ13   | Φ25   | Φ16.5 | 115 | 59     | Φ30   | 5.5   |

|              |                |     |       |     |     |       |    |
|--------------|----------------|-----|-------|-----|-----|-------|----|
| DTL-2-185-13 | Φ13            | Φ32 | Φ18.5 | 122 | 60  | Φ35   | 6  |
| DTL-2-240-13 | Φ13            | Φ32 | Φ21   | 122 | 60  | Φ35   | 6  |
| DTL-2-300-13 | Φ13            | Φ34 | Φ23.5 | 128 | 65  | Φ35   | 6  |
| DTL-2-400-17 | Φ17            | Φ40 | Φ26   | 160 | 90  | Φ36   | 6  |
| DTL-2-500-17 | Round Head Φ17 | Φ40 | Φ30   | 160 | 95  | Φ36   | 6  |
| DTL-2-500    | Squire Head    | Φ47 | Φ30   | 205 | 95  | 60*60 | 10 |
| DTL-2-630-17 | Round Head     | Φ47 | Φ33.5 | 205 | 95  | 60    | 10 |
| DTL-2-630    | Squire Head    | Φ47 | Φ33.5 | 205 | 95  | 60*60 | 10 |
| DTL-2-800    | Round Head     | Φ60 | Φ38.5 | 240 | 110 | 80    | 10 |
| DTL-2-800    | Squire Head    | Φ60 | Φ38.5 | 240 | 110 | 80*80 | 10 |
| DTL-2-1000   | Round Head     | Φ60 | Φ43.5 | 240 | 110 | 80    | 10 |
| DTL-2-1000   | Squire Head    | Φ60 | Φ43.5 | 240 | 110 | 80*80 | 10 |

### Product Feature And Application

|                      |   |
|----------------------|---|
| Material:            | Aluminum L3 and copper T2   |
| Working temperature: | -55℃ to +150℃   |
| Application:         | Terminal connectors are used to connect tap conductor to power equipments (transformer, circuit breaker, disconnect switch etc) or to wall bushing of substation. |

Selling Units: Single item

Single package size: 9X2.5X2.5 cm

Single gross weight: 0.19 kg

Package Type: Box, Carton, Pallet or Crate

### Lead Time:

|                 |        |          |            |                  |
|-----------------|--------|----------|------------|------------------|
| Quantity(Piece) | 1 - 10 | 11 - 500 | 501 - 1000 | >1000            |
| Est. Time(days) | 15     | 20       | 30         | To be negotiated |

### Product Details



