



S31803 2205 Duplex Steel Pipe For Oil Refinery

Zhejiang Bewell Steel Industry Co., Ltd. is a professional Bewell® S31803 2205 Duplex Steel Pipe For Oil Refinery and stainless steel seamless pipe manufacturer in China, our company has been trusted by customers at home and abroad from the continuous exploration to the automation and intelligence of equipment, standardization, systematization and standardization of production today, choose Bewell, let you rest assured.

Product Description

Bewell® Duplex stainless steel is in its solid solution organization in the ferrite phase and austenite phase about half, the Bewell® steel has both austenitic and ferritic stainless steel characteristics, compared with ferrite, plasticity, toughness, no room temperature brittleness, intergranular corrosion resistance and welding performance are significantly improved, compared with austenitic stainless steel, high strength and resistance to intergranular corrosion and chloride stress corrosion has significantly improved.

Parameter(Specification) of the Bewell® S31803 2205 Duplex Steel Pipe For Oil Refinery

Product	Bewell® Seamless Pipe	
Seamless Pipe	China	GB/T8162/T8163 GB5310/6579/9948
	U.S.A.	ASTM A53/A106/A178/A179/A192/A210/A213/A333/A335/A283/A135/A214/315/A500/A501/A519/A161/A334; API 5L/5CT
	Japan	JIS G3452/G3454/G3456/G3457/G3458/G3460/3461/3462/3464
	Germany	DIN 1626/17175/1629-4/2448/2391/17200 SEW680
	Russia	GOST 8732/8731/3183
Material	China	10#, 20#, 16Mn, 20G, 15MoG, 15CrMo, 30CrMo, 42CrMo, 27SiMn, 20CrMo

Zhejiang Bewell Steel Industry Co.,Ltd.

Phone:+86-18072196625

E-mail: bwss@vip.163.com

and Grade	U.S.A.	Gr. B/Gr.A/A179/A192/A-1/T11/T12/T22/P1/FP1/T5/4140/4130
	Japan	STPG38,STB30,STS38,STB33,STB42,STS49,STBA23,STPA25,STPA23
	German	ST33,ST37,ST35,ST35.8,ST45,ST52,15Mo3,13CrMo44, 1.0309, 1.0305, 1.0405
	Russia	10, 20, 35, 45, 20X
Out Diameter	10-1000mm	
Wall Thickness	1-80mm	
Length	1-12m	
Protection	Plastic caps	
Packing terms	Labeled and bundled together with steel strip	
Shipment terms	Containers or bundles by sea,one 20" container can load about 20 tons(5.8meters long),one 40" container can load about 23-25tons(less than 11.8meters long)	
Quality Certificate	ISO, API, Mill Test Certificate	
Surface Treatment	Black painting/varnished surface,anti-corrosion oil, galvanized or as per required by customer	

Technique	Hot Rolled/Cold Drawn
Steel grades	Q195, Q235A-B, Q345A-E, 20#, 10#,16Mn, ASTM A36,ASTM A500, ASTM A53, ASTM 106, SS400, St37, St52, S235JR, S355TRH ect.
Standards	GB/T 3091-2001,GB/T13912-2002, BS 1387, ASTM F1083 ect.
Pipe ends	plain, beveled, threaded, socket with holes, with PVC clap/ coupling/ clamp, or as customers' requirement
treatment	

Application	liquid delivery (pump well, gas, water), construction pipe, structural pipe(greenhouse structure, fence post), curtain wall, machinery part ect.
Delivery Time	10days from stock; 15-20days produced according to the qty
Payment Term	T/T or L/C
Price Term	CIF; CFR; FOB

Feature and application of the Bewell® S31803 2205 Duplex Steel Pipe For Oil Refinery

Features:

Good resistance to pore corrosion
Good overall mechanical properties
Good solderability
High heat transfer efficiency

Application scenarios:

**APPLICATION
FIELD**



WATER PIPE



Details of the Bewell® S31803 2205 Duplex Steel Pipe For Oil Refinery



