

NVF4-1 & NVF4-2



NVF4-1 NVF4-2 NVF4-2b
 26.5×26.5×24.5(+15.5) 35.5×35.5×45.5(+22.5)

Features
<ul style="list-style-type: none"> Small size and light weight. Heavy contact load (40A). Suitable for automobile and lamp accessories application. PC board mounting and direct insert mounting available.

Ordering Information
<u>NVF4-1 C - Z 30 b DC12V 1.6 D</u>
1 2 3 4 5 6 7 8
1 Part number: NVF4-1 NVF4-2(Plastic Bracket), NVF4-2a(With Metal Bracket) NVF4-2b(Shrouded With Metal Bracket) 2 Contact arrangement: A:1A1; A2:1A2; B:1B; C:1C; C2:1C2 3 Enclosure: S: Wash tight ; Z: Dust protected 4 Contact current: A Form: 20A,40A; B Form: 20A,30A; C Form or C2 Form: 15A,20A, 30A, 40A; A2 Form: 2×20A 5 Terminals: b: PCB type; a1: plug in type 1; a2:plug in type 2 6 Coil rated voltage(V): DC:6,9,12,24,48 7 Coil power: 1.6:1.6W; 1.9:1.9W; 2.3:2.3W; 2.6:2.6W 8 Coil transient suppression: D: with diode R: with resistance NIL: standard

Contact Data		1A(SPSTNO) 1B(SPSTNC) 1C(SPDT(B-M))			
Contact Arrangement		1A(SPSTNO) 1B(SPSTNC) 1C(SPDT(B-M))			
Contact Material		AgSnO ₂			
Contact Rating (Resistive)		1A1	1B	1C or C2	1A2
		40A/14VDC 20A/24VDC	30A/14VDC 20A/24VDC	NO:40A/14VDC NC:30A,40A/14VDC 15A,20A/24VDC	2×20A/14VDC
Max. Switching Power		630W			
Max. Switching Voltage		75VDC		Max. Switching Current:40A	
Voltage Drop(Initial)		Typ: 50mV (at 10A)		Item 4.12 of IEC 61810-7	
Operation Life	Electrical	1×10 ⁵		Item 4.30 of IEC 61810-7	
	Mechanical	1×10 ⁷		Item 4.31 of IEC 61810-7	

NOTE: Limiting continuous current at 125°C:NC/NO:10A/15A.

Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pick-up voltage VDC(max) (65%of rated voltage)	Drop-out voltage VDC(min) (10% of rated voltage)	Coil power W	Operate time ms	Release time ms
	Rated	Max.						
006-1600	6	7.8	22.5	3.9	0.6	1.6	≤7	≤5
009-1600	9	11.7	50.6	5.9	0.9			
012-1600	12	15.6	90	7.8	1.2			
024-1600	24	31.2	360	15.6	2.4			
048-1600	48	62.4	1440	31.2	4.8			
006-1900	6	7.8	19	3.9	0.6	1.9		
012-1900	12	15.6	75.8	7.8	1.2			
024-1900	24	31.2	303.2	15.6	2.4			
006-2300	6	7.8	15.6	3.9	0.6	2.3		
012-2300	12	15.6	62.6	7.8	1.2			
024-2300	24	31.2	250.4	15.6	2.4			
006-2600	6	7.8	13.8	3.9	0.6	2.6		
012-2600	12	15.6	55.4	7.8	1.2			
024-2600	24	31.2	221.5	15.6	2.4			

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
 2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

