Sample of CNC Grinding Part

Welcome to buy Sample of CNC Grinding Part from SJ. Our company has vast experience in manufacturing high precision Grinding rod, turned and milled parts, stamping parts, machined plastic parts . This High precision Grinding rod was processed by cnc machining center. The raw material was purchased from a reliable famous material factory. All of the parts which we manufactured were executed 100% inspection before deliver to our clients. Furthermore, we provide Material Data Sheet,QC Inspection Report, ROHS Report along with the products to the customer.

Product Description

Wholesale quality Sample of CNC Grinding Part. SJ is a Sample of CNC Grinding Part manufacturer and supplier in China. Provide professional after-sales service and the right price, looking forward to cooperation.

Product parameter (Specification) of High precision Grinding rod:

1.Material of High precision Grinding rod: SS304, SS 316, SS301, AL2024, AL5052, AL 6061, AL 6063, AL7075, 12L14, 1213, C3600, C3771 etc.
2.Surface treatment of high precision Grinding rod: Polishing, Mirror polishing, Anodized, Hard anodizing, Oil painting, Powder painting, Galvanized, Nickel plating etc.
3.Packaging: neutral packing, blister and bubble plastic bag. Or packing as per clients' request.
4.Delivery time: 7-10 days for sample orders, 15-25 days for mass production orders.
5.Payment terms: T/T, By Paypal, By Western Union.
6.Processing machines: Lathe machine, Milling machine, CNC machining center, Grinder etc.

Dongguan Senjing Metal Technology Co.,Ltd.
Phone:+86-13538188717
E-mail: sales@cncpartsj.com

Pictures of Our Workshops(Lathe, Auto-lathe, CNC machining center)

Dongguan Senjing Metal Technology Co.,Ltd.
Phone:+86-13538188717
E-mail: sales@cncpartsj.com

Dongguan Senjing Metal Technology Co.,Ltd.
Phone:+86-13538188717
E-mail: sales@cncpartsj.com

Dongguan Senjing Metal Technology Co.,Ltd.
Phone:+86-13538188717
E-mail: sales@cncpartsj.com

Our Procedures for Manufacturing the Parts:

1.The customer provide a sample or drawing(in stp, step, igs, pdf or cad format) to us, these information must be very clear ie. Material , Surface treatment, Tolerance, Order quantity,special requirement, packaging requirement etc.
2.After our sales translated some notes on the drawing into Chinese, our engineer will evaluate the production cost for the part. If there are any questions or problems on the drawing, we will communicate with the client at once by email or by Whatsapp. We will audit the price and send quotation to the client ASAP.
3.Negotiate with the client about the order and confirm the payment terms, delivery time and shipping cost. We always try our best to provide best service to our clients, if they need a shipping agent, we will recommend a reliable and trustworthy one for them to make sure deliver the goods timely and costly.
4.During production, our sales will update the status weekly by email.
5.Once finish production, we will inform you to pay the balance, then arrange the shipment for you.
6.After the client receive the products, please give us feedback about our product quality. If the parts were damaged or ruined during shipment, we would arrange new one to replace of bad parts for our clients.

Q&A:

1. Q: What is Passivation?
A:The passivate process is designed to remove foreign metals and oils (usually from machining) from the surface of stainless steel. The end finish will not change the dimension of the part nor the overall appearance of the base metal. Passivation purifies the surface of a machined part and therefore improves corrosion resistance.

2.Q: What is black zinc plating?
A: Black zinc plating is used to provide corrosion protection and anti-galling properties to parts in high wear, high temperature, and corrosive environments. It is achieved by applying zinc plating followed by black chromate conversion plating. The result is a uniform, durable coating providing corrosion and wear resistance as well as anti-galling properties. The surface color can range from matte to different iridescent hues. Black zinc plating is thicker than other plating methods, which may affect the dimensions of tight fitting parts.